

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35, T. 25 S., R. 5 W.

CHAINS  
58.94

Point for the center N 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} C \\ C \text{ N } 1/16 \text{ S } 35 \\ C \\ 1963 \end{array}$$

from which

A fir, 33 ins. diam., bears N. 40° E., 314 lks. dist., mkd. C N 1/16 S35 BT.

A fir, 23 ins. diam., bears S. 69° E., 173 lks. dist., mkd. C N 1/16 S35 BT.

Ascend 55 ft. over S. slope.

62.00 Spur, slopes SW.; desc. 225 ft. over NW. slope, entering medium timber and moderate undergrowth.

67.20 Ravine, drains NW.; desc. 175 ft. over broken NW. slope.

77.90 Creek, 2 lks. wide, course N. 30° W.; desc. 5 ft. over creek bottom.

78.56 The ¼ sec. cor. of secs. 26 and 35.

From the ¼ sec. cor. of secs. 35 and 36.

S. 89° 35' W., on the E. and W. center line of sec. 35.

Descend 175 ft. over SW. slope, through medium timber and light undergrowth.

0.80 Leave timber, enter open prairie, edge bears NE. and SW.

6.85 Gully, 3 lks. wide, 5 ft. deep, drains S. 30° W.; desc. 50 ft. over broken SW. slope.

14.60 Spur, slopes S. 30° W.; desc. 140 ft. over W. slope, entering scattering timber and light undergrowth.

17.85 Ravine, drains S. 30° W.; desc. 235 ft. over SW. slope.

33.15 Creek, 4 lks. wide, course W., from S. 80° E.

34.30 Leave creek, course N. 70° W.; asc. 25 ft. over NE. slope.

35.50 Dirt road, 10 lks. wide, bears N. 60° W. and S. 60° E.

38.35 Spur, slopes N.; desc. 35 ft. over W. slope.

39.35 Enter a draw, drains N.; continue over level bottom.

39.65 Creek, 2 lks. wide, course N.

39.97 The center ¼ sec. cor. of sec. 35, in a new wire fence which bears N. and S.

40.25 Leave draw; asc. 120 ft. over broken NE. slope.

48.70 Spur, slopes N. 30° W.; desc. 100 ft. over SW. slope.

52.25 Creek, 3 lks. wide, in a ravine, course NW.; asc. 265