

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 26 S., R. 3 W.

CHAINS

Beginning at the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., remonumented by Zirpel in 1959, with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, protruding 7 ins. above the ground, with brass cap marked

T 26 S	
R 3 W	R 2 W
S 1	S 6
S 12	S 7
1959	

from which the remaining original bearing tree

A fir stump, 30 ins. diam., bears N. 46° W., 88 lks. dist., with scribe marks T26S R3W S1 visible on partially opened blaze.

and 1959 bearing trees

A hemlock, 10 ins. diam., bears N. 37° E., $17\frac{1}{2}$ lks. dist., mkd. T26S R2W S6 BT.

A cedar, 12 ins. diam., bears S. 73° E., 41 lks. dist., mkd. T26S R2W S7 BT.

add one new bearing tree

A fir, 35 ins. diam., bears S. 66° W., 123 lks. dist., mkd. T26S R3W S12 BT.

N. 0° 18' E., bet. secs. 1 and 6, marking and blazing the true line.

Ascend 204 ft. over broken SE. slope, through old logged area.

20.085 Point for the S 1/16 sec. cor. of secs. 1 and 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked

S 1/16	
S 1	S 6
1963	

from which

A fir, 18 ins. diam., bears S. 44° E., 164 lks. dist., mkd. S 1/16 S6 BT.

A cedar, 35 ins. diam., bears N. $10\frac{1}{2}^{\circ}$ W., 93 lks. dist., mkd. S 1/16 S1 BT.

Ascend 196 ft. over S. slope, along W. edge of heavy timber.

40.17 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, determined at record bearing and distance from one bearing tree marked by Collier, in 1913:

A fir snag, 40 ins. diam., bears S. 88° E., 22 lks. dist., with scribe marks BT visible on bark blaze.

and a local bearing tree

A fir, 50 ins. diam., bears N. 2° W., 47 lks.