

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 26 S., R. 3 W.

CHAINS

dist., mkd. $\frac{1}{4}$ S1 CS BT on bark blaze.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S 1} | \text{S 6} \\ \text{R 3 W} | \text{R 2 W} \\ \text{T 26 S} \\ 1963 \end{array}$$

from which a new bearing tree

A cedar, 18 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ E., 41 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

The cor. falls on top of a ridge, bears NE. and SW.

N. 1° 15' E., beginning new measurement.

Descend 477 ft. over NW. slope, changing to broken W. slope, through heavy timber and moderate undergrowth.

- 18.50 Ravine, drains W. at base of rock bluff; base bears NW. and SE. Ascend 63 ft. over face of bluff.
- 21.60 Top of bluff bears NW. and SE.; asc. 32 ft. over SW. slope.
- 23.40 Top of steep rock bluff bears SW. and N. along line; asc. 45 ft. along bluff top.
- 26.00 Top of ascent on bluff top; desc. 76 ft. along bluff.
- 36.90 N. end of bluff; desc. 42 ft. over NW. slope.
- 39.87 The corner of townships 25 and 26 south, ranges 2 and 3 west, monumented with an iron post, 3 ins. diam., firmly set, protruding 8 ins. above the ground, with brass cap marked and witnessed as described in the official record.
- Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, pine, maple, chinquapin, madrone, dogwood; undergrowth, hazel, salal, poison oak, vine maple, blackberry, and fern.
-
- Dependent Resurvey of a Portion of the N. Bdy.,
T. 26 S., R. 3 W.
(Restoring the 1855 survey by Addison R. Flint,
and the 1943 resurvey by Norman D. Price)
-
- From the corner of townships 25 and 26 south, ranges 2 and 3 west.
- N. 89° 05' W., bet. secs. 1 and 36, marking and blazing the true line.
- Descend 365 ft. over W. slope, through moderate timber and undergrowth.
- 9.88 Rock Creek, 100 lks. wide, course S.; asc. 233 ft. over broken E. slope.