

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion, of E. Bdy., T. 26 S., R. 3 W.

CHAINS
16.07

Rock Creek Road, bituminous pavement, 32 lks. wide, bears N. and S.; enter old logged area with dense undergrowth.

39.50

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with an iron pipe, 2 ins. diam., firmly set, protruding 10 ins. above the ground, at record bearing and distance from the bearing trees mkd. by Norman D. Price in 1943:

A sawed fir stump, 18 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ E., 74 lks. dist., mkd. S on partially opened blaze.

A sawed fir stump, 24 ins. diam., bears S. $77\frac{1}{2}^{\circ}$ W., 63 lks. dist., mkd. $\frac{1}{4}$ S on partially opened blaze.

and a locally established bearing tree

A hemlock, 28 ins. diam., bears N. $54\frac{1}{2}^{\circ}$ E., 29 lks. dist., mkd. $\frac{1}{4}$ S36 253 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 25 S

R 3 W

 $\frac{1}{4}$ S 36 $\frac{1}{4}$ S 1

T 26 S

1963

from which a new bearing tree

A fir, 10 ins. diam., bears S. 47° E., 103 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Reset iron pipe alongside iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W.

(Restoring the 1855 survey by Addison R. Flint,
the 1877 and 1879 surveys by William H. Byars,
and the 1882 survey by Samuel C. Flint)

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.

N. $88^{\circ} 09'$ W., bet. secs. 1 and 12, marking and blazing the true line.

Ascend 49 ft. along broken S. slope, through heavy timber and moderate undergrowth, along the S. edge of old logged area.

0.93 Dirt road, 20 lks. wide, bears NW. and SE.

13.90 Spur, slopes 70° W.; desc. 85 ft. over broken W. slope.

19.87 Point for the E $1/16$ sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap marked