

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

34.00 Ravine drains N.; asc. 8 ft. over E. slope.

40.19 The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded in 1960, by J. W. Byron, County Surveyor, monumented with an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, protruding 18 ins. above the ground, with a brass cap marked

T 26 S R 3 W

S 2 | S 1

S 11 | S 12

1960

FD. OK 1/10/78 - G. LANGRISH  
Dou. Co. Surveyor Office  
C.S. 59/46

from which the remains of the original bearing trees

A fir, 42 ins. diam., bears N.  $55^{\circ}$  E., 61 lks. dist., (58 lks. to face), with scribe marks visible on bark blaze. (Record bearing and distance, N.  $48^{\circ}$  E., 58 lks.)

A fir, 42 ins. diam., bears S.  $86\frac{3}{4}^{\circ}$  W., 66 lks. dist., with a healed blaze. (Record bearing, S.  $88^{\circ}$  W.)

A fir, 60 ins. diam., bears N.  $24\frac{1}{4}^{\circ}$  W., 150 lks. dist., mkd. S2 T26S R3W B on bark blaze. (Record bearing, N.  $45^{\circ}$  W.)

and bearing trees marked by the County Surveyor in 1960

A fir, 8 ins. diam., bears N.  $62\frac{3}{4}^{\circ}$  E., 39 lks. dist., with a partially healed blaze.

A fir, 19 ins. diam., bears S.  $78\frac{1}{2}^{\circ}$  E., 27 lks. dist., with a partially healed blaze.

A fir, 8 ins. diam., bears N.  $54\frac{3}{4}^{\circ}$  W.,  $24\frac{1}{2}$  lks. dist., mkd. T26S R3W S2 CS BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, pine, oak, maple, dogwood, chinquapin, and madrone; undergrowth, vine maple, arrowwood, blackberry, poison oak, salmonberry, hazel, and fern.

N.  $1^{\circ}$  14' E., bet. secs. 1 and 2.

Descend 276 ft. over NW. slope, through heavy timber and moderate undergrowth.

16.95 Left bank of the North Umpqua River, 240 lks. wide, course West.

19.34 Right bank of the North Umpqua River; asc. 7 ft. over S. slope.

19.91 The S  $1/16$  sec. cor. of secs. 1 and 2, at record bearing and distance from the witness corner to the S  $1/16$  sec. cor. of secs. 1 and 2, established by J. W. Byron, Deputy County Surveyor, in 1960.

At the corner point

Set an iron post, 25 ins. long, 1 in. diam., 20 ins. in the ground, with brass cap marked