

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

S 1/16

S 2 | S 1

T 26 S | R 3 W

1963

21.23 North Umpqua Highway, bituminous pavement, 32 lks. wide, bears E. and W.

21.58 The witness corner to the S 1/16 sec. cor. of secs. 1 and 2, established by Byron, monumented with an iron rod,  $\frac{1}{2}$  in. diam., set flush with pavement in a parking lot, from which Byron's bearing tree

A fir, 26 ins. diam., bears N.  $37^{\circ}$  W., 126 lks. dist., with a healed blaze.

Ascend 249 ft. over S. slope.

22.18 7-wire utility line, bears E. and W. along highway; enter scattering timber and dense undergrowth.

28.15 Three-wire transmission line, bears N.  $80^{\circ}$  E. and S.  $80^{\circ}$  W.

39.82 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 2, perpetuated and recorded by A. Boyer, County Surveyor, in 1937, monumented with a shotgun barrel in a mound of stone, and rehabilitated by J. Byron, Deputy County Surveyor, in 1960, from which the remains of the bearing trees marked by Boyer:

A fir stump, 26 ins. diam., bears N.  $26\frac{1}{2}^{\circ}$  E., 43 lks. dist., with a healed blaze.

A fir stump, 24 ins. diam., bears S.  $83\frac{1}{2}^{\circ}$  E., 23 $\frac{1}{2}$  lks. dist., with a healed blaze.

and bearing trees mkd. in 1960

A fir, 17 ins. diam., bears S.  $40^{\circ}$  E., 30 lks. dist., with a healed blaze.

A fir, 8 ins. diam., bears S.  $74^{\circ}$  W., 7 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

 $\frac{1}{4}$ 

S 2 | S 1

T 26 S | R 3 W

1963

Deposit shotgun barrel alongside the iron post.

N.  $0^{\circ}$  51' E., beginning new measurement.

Ascend 351 ft. over S. slope, across logged area through moderate undergrowth, along fence line; fence extends N. and E.

18.80 Point for the N 1/16 sec. cor. of secs. 1 and 2.