

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{N } 1/16 \\ \text{S } 2 \mid \text{S } 1 \\ \text{T } 26 \text{ S } \mid \text{R } 3 \text{ W} \\ 1963 \end{array}$$

from which

A fir, 13 ins. diam., bears N.  $50^{\circ}$  E., 53 lks. dist., mkd. N 1/16 S1 BT.

A fir, 23 ins. diam., bears S.  $68\frac{1}{4}^{\circ}$  W., 37 lks. dist., mkd. N 1/16 S2 BT.

From this point a squared wood stake, 2 ins. square, firmly set, protruding 26 ins. above the ground, bears N.  $88^{\circ} 30'$  W., 0.27 chs. dist., set by the Weyerhauser Co.

Ascend 32 ft. over SE. slope, through heavy timber and moderate undergrowth.

23.50 Spur slopes E.; asc. 8 ft. along broken E. slope.

30.90 Creek, 2 lks. wide, course S.  $30^{\circ}$  E.; asc. 109 ft. over SW. slope.

37.96 The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above the ground, with brass cap marked and witnessed as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, maple, oak, madrone, dogwood, chinquapin, and alder; undergrowth, hazel, vine maple, blackberry, ocean spray, poison oak, fir reproduction, fern, and salal.

From the cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by J. W. Byron, County Surveyor, in 1960, monumented with an iron post, 1 in. diam., firmly set, protruding 18 ins. above the ground, with brass cap marked

$$\begin{array}{c} \text{T } 26 \text{ S } \text{R } 3 \text{ W} \\ \text{S } 15 \mid \text{S } 14 \\ \text{S } 22 \mid \text{S } 23 \\ 1960 \end{array}$$

from which the remains of the original bearing trees

A down and partly rotted fir, 40 ins. diam., bears S.  $87^{\circ}$  E., 50 lks. dist., with a burned face bearing old axe marks.

A fir, 43 ins. diam., bears S.  $39^{\circ}$  W., 26 lks. dist., with a healed blaze. (Record bearing, S.  $30^{\circ}$  W.)

A fir snag, 40 ins. diam., bears N.  $52^{\circ}$  W., 37 lks. dist., (40 lks. on slope), with scribe marks T26S R3W S15 BT on bark blaze. (Record