

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

bearing and distance, N. 50° W., 40 lks.)

and bearing trees marked by A. Boyer, in 1944

A chinquapin, 12 ins. diam., bears N. 71° E.,  
40 lks. dist., with scribe marks 14 26S R3W S BT  
visible on partially healed blaze.

A fir, 12 ins. diam., bears S. 71° E., 35 lks.  
dist., with a healed blaze.

and bearing trees marked by J.W. Byron, in 1960

A fir, 6 ins. diam., bears S. 22½° E., 5½ lks.  
dist., with fragmentary scribe marks visible on  
partially healed blaze.

A hemlock, 8 ins. diam., bears N. 80° W., 26 lks.  
dist., with scribe marks 26S R3W S15 CS BT  
visible on partially healed blaze.

N. 2° 20' W., bet. secs. 14 and 15.

Descend 201 ft. over NW. slope, through scattering  
timber and dense undergrowth.

10.69 Spring, drains N. 20° W.; desc. 7 ft. over NW. slope.

12.40 Britt Creek, 10 lks. wide, from SW. course NW.; desc.  
58 ft. over broken NW. slope.19.29 Britt Creek, 10 lks. wide, course N. 10° E., curving  
N.; desc. 9 ft. over broken NW. slope.

20.47 Point for the S 1/16 sec. cor. of secs. 14 and 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.  
in the ground, to bedrock, and in a mound of stone, 3  
ft. base, to top, with brass cap marked

S 1/16  
S 15 | S 14  
1962

from which

A fir, 19 ins. diam., bears N. 18° E., 39 lks.  
dist., mkd. S 1/16 S 14 BT.

A cedar, 17 ins. diam., bears S. 63° W., 52 lks.  
dist., mkd. S 1/16 S15 BT.

From this point an iron pipe, 2 ins. diam., firmly set,  
protruding 24 ins. above the ground, bears West, 0.23  
chs. dist.Descend 51 ft. over NE. slope, along E. edge of old  
logged area, through Britt Creek bottom.

22.14 Leave Britt Creek bottom, course NE.

29.26 Britt Creek, 10 lks. wide, course NW.; desc. 1 ft. over  
broken NW. slope.

33.19 Ravine drains W.; asc. 67 ft. over SW. slope.