

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS  
81.88

The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by G.G. Stewart, County Surveyor, in 1922, monumented with an iron pipe, 1 in. diam., firmly set, protruding 1 in. above the ground, from which the remains of the original bearing trees:

A rotted fir stump shell, 18 ins. diam., bears N. 70° E., 23 lks. dist. (Record bearing, N. 72° E.)

A fir, 23 ins. diam., bears S. 72° W., 11 lks. dist., with old scars and rotted center.

A fir, 40 ins. diam., bears N. 46° W., 27½ lks. dist., (25 lks. to face) with scribe marks T26 R3 S10 BT on recent bark blaze. (Record distance, 25 lks.)

and the County Surveyor's bearing trees

A fir snag, 33 ins. diam., bears N. 32° E., 33 lks. dist., with various old scars.

A fir, 34 ins. diam., bears S. 58° E., 66 lks. dist., with scribe marks CS S14 BT on bark blaze.

A yew, 13 ins. diam., bears S. 41° W., 29 lks. dist., with fragmentary scribe marks on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T 26 S R 3 W			
S 10		S 11	
S 15		S 14	
1962			

from which a new bearing tree

A cedar, 21 ins. diam., bears N. 47° E., 110 lks. dist., mkd. T26S R3W S11 BT.

Reset the County Surveyor's iron pipe inside the iron post.

Land, hilly.

Soil, rocky clay loam.

Timber, fir, cedar, pine, chinquapin, maple, alder, yew, madrone, and dogwood; undergrowth, vine maple, Oregon grape, hazel, fern, arrowwood, poison oak, tan-oak, huckleberry, marsh grass, salal, and sweet pea.

From the cor. of secs. 21, 22, 27, and 28, perpetuated and recorded by J. W. Byron, County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above the ground, with brass cap marked

T 26 S R 3 W			
S 21		S 22	
S 28		S 27	
1959			

from which the remains of the original bearing trees