

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS	
	<p>A black oak snag, 22 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ E., 996 lks. dist., with scribe marks S22 visible on partially opened and rotted blaze. (Record bearing and distance, N. 5° E., 1009 lks.)</p> <p>A badly burned and chopped madrone stump shell, approximately 40 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ W., 265 lks. dist. (Record bearing and distance, S. 5° W., 268 lks.)</p> <p>A down and rotted white oak, 24 ins. diam., lies on the ground, at a point which bears N. 23° W., 447 lks. dist., with portions bearing old scribe marks lying alongside. (No evidence of a stump hole nearby. Record bearing and distance, N. 20° W., 480 lks.)</p> <p>and the County Surveyor's bearing trees</p> <p>A cedar, 29 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ E., 26 lks. dist., mkd. T26S R3W S22 CS BT.</p> <p>A cedar, 27 ins. diam., bears S. 84° E., 29 lks. dist., mkd. T26S R3W S27 CS BT.</p> <p>A cedar, 7 ins. diam., bears S. 72° W., 16 lks. dist., mkd. T26S R3W S28 CS BT.</p> <p>A fir, 14 ins. diam., bears N. 66° W., 39 lks. dist., with scribe marks visible on partially healed blaze.</p> <p>Corner point was determined by the County Surveyor's Office as to best fit the original evidence remaining in 1959.</p> <p>N. 0° 22' E., bet. secs. 21 and 22.</p> <p>Ascend 348 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p>
14.08	Draw drains SE.; leave timber, edge bears SE. and N. enter dense undergrowth; asc. 38 ft. over SW. slope.
20.125	<p>Point for the S $1/16$ sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">S $1/16$ S 21 S 22 1962</p> <p>from which</p> <p>A cedar, 9 ins. diam., bears N. $28\frac{3}{4}^{\circ}$ E., 35 lks. dist., mkd. S $1/16$ S22 BT.</p> <p>A cedar, 13 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. S $1/16$ S21 BT.</p> <p>Ascend 105 ft. over SE. slope.</p>
26.56	Spur, slopes SE.; asc. 12 ft. along broken E. slope.
35.26	Top of ascent, slopes E.; desc. 79 ft. over broken NE. slope.