

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 26 S., R. 3 W.

CHAINS	
12.58	Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.
14.95	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
18.85	Top of ascent, slopes N.; desc. 7 ft. over NW. slope.
20.395	Point for the E 1/16 sec. cor. of secs. 15 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked
	$E \frac{1}{16} \frac{S \ 15}{S \ 22}$ 1962
	from which
	A hemlock, 6 ins. diam., bears N. 16° W., 46 lks. dist., mkd. E 1/16 S15 BT.
	A fir, 22 ins. diam., bears S. 75° E., 26 lks. dist., mkd. E 1/16 S22 BT.
	Descend 25 ft. over NW. slope.
23.10	Creek, 3 lks. wide, course NE.; asc. 161 ft. over NE. slope.
33.39	Draw, drains NE.; asc. 84 ft. over NE. slope.
40.79	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked
	$\frac{1}{4} \frac{S \ 15}{S \ 22}$ 1962
	from which
	A fir, 48 ins. diam., bears N. 5° W., 125 lks. dist., mkd. ¼ S 15 BT.
	A cedar, 17 ins. diam., bears S. 51° E., 80 lks. dist., mkd. ¼ S22 BT.
	Ascend 25 ft. over NE. slope.
41.39	Top of ascent, slopes N.; desc. 379 ft. over NW. slope.
54.05	Creek, 3 lks. wide, course NW.; desc. 13 ft. over broken NW. slope.
60.68	Foot of descent, slopes N.; asc. 22 ft. over NE. slope.
62.96	Spur, slopes NE.; desc. 149 ft. over steep NW. slope.
69.16	Creek, 5 lks. wide, course NE.; asc. 83 ft. over NE. slope.
74.72	Spur, slopes NE.; desc. 5 ft. over NW. slope.
76.17	Draw, from W. drains NE.; asc. 91 ft. over broken E. slope.