

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS	
	<p>Land, hilly. Soil, rocky clay loam. Timber, fir, cedar, pine, oak, yew, maple, ash, chinquapin, dogwood, alder, madrone, hemlock, and tanoak; undergrowth, vine maple, manzanita, poison oak, Oregon grape, salal, huckleberry, fern, arrowwood, sweet pea, hazel, and marsh grass.</p>
	<p>S. $89^{\circ} 55'$ W., bet. secs. 10 and 15.</p> <p>Descend 273 ft. over SW. slope, through scattering timber and moderate undergrowth.</p>
13.25	Ravine, drains SW.; desc. 61 ft. over SW. slope.
15.91	Britt Creek, 10 lks. wide, course NW.; asc. 46 ft. over NE. slope.
19.80	<p>Point for the E $\frac{1}{16}$ sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">E $\frac{1}{16}$ $\frac{S}{S}$ $\frac{10}{15}$ 1962</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 17 lks. dist., mkd. E $\frac{1}{16}$ S10 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 82° W., 6 lks. dist., mkd. E $\frac{1}{16}$ S15 BT.</p> <p>From this point an iron pipe, $\frac{3}{4}$ ins. diam., firmly set protruding 4 ins. above the ground, bears N. $51\frac{1}{2}^{\circ}$ W., 0.045 chains dist.</p> <p>Ascend 19 ft. over NE. slope.</p>
23.58	An iron pipe, $\frac{1}{2}$ in. diam., firmly set, protruding 3 ins. above the ground, on line, and in E. and W. fence line.
24.77	Top of ascent, slopes N.; desc. 133 ft. over NW. slope.
35.25	Graveled road, 15 lks. wide, bears N. and S.
35.65	Four strand barbed wire fence extends N.
35.78	Creek, 4 lks. wide, course NW. from SW.; asc. 69 ft. over E. slope.
39.60	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, reestablished by proportionate measurement, by A. R. Evans, Registered Engineer Number 2741, in 1951, monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, protruding 4 ins. above the ground, from which the bearing trees marked by Evans:</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 67° W., 24 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 1° W., 26 lks. dist., with a healed blaze.</p> <p>At the corner point</p>