

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, 26 S., R. 3 W.

## CHAINS

- 46.55 Spur, slopes S.; desc. 43 ft. over rolling SW. slope.
- 58.70 Enter heavy timber, edge bears N. and S.
- 63.30 Enter open rolling prairie, edge bears approximately N. and S.
- 66.50 Spur, slopes S.  $40^{\circ}$  W.; desc. 140 ft. over NW. slope.
- 79.84 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T 26 S R 3 W
S 20   S 21
S 29   S 28
1963

from which

A fir, 12 ins. diam., bears N.  $25\frac{1}{4}^{\circ}$  E., 45 lks. dist., mkd. T26S R3W S21 BT.

A black oak, 14 ins. diam., bears S.  $26\frac{1}{4}^{\circ}$  E., 31 lks. dist., mkd. T26S R3W S28 BT.

A fir, 8 ins. diam., bears S.  $56\frac{1}{2}^{\circ}$  W., 37 lks. dist., mkd. T26S R3W S29 BT.

A fir, 15 ins. diam., bears N.  $80\frac{3}{4}^{\circ}$  W., 50 lks. dist., mkd. T26S R3W S20 BT.

From this point the cor. of secs. 28, 29, 32, and 33 bears S.  $0^{\circ} 25'$  E., 80.18 chains dist., determined at record bearing and distance from one original bearing tree:

A white oak, 39 ins. diam., bears S.  $37^{\circ}$  W., 356 lks. dist., with opened and rotted blaze.

and bearing trees marked by Floyd Frear, County Engineer, in 1949

A white oak, 15 ins. diam., bears S.  $7\frac{1}{2}^{\circ}$  E., 188 lks. dist., with a healed blaze.

A white oak, 29 ins. diam., bears S.  $46^{\circ}$  W., 193 lks. dist., with a healed blaze.

At the corner point

Bury an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., the top 18 ins. below the surface of the ground, with brass cap marked

T 26 S R 3 W
S 29   S 28
S 32   S 33
1963

from which

A white oak, 10 ins. diam., bears N.  $17\frac{1}{4}^{\circ}$  E., 349 lks. dist., mkd. T26S R3W S28 BT.