

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

A white oak, 30 ins. diam., bears N. $65\frac{1}{4}^{\circ}$ W.,
327 lks. dist., mkd. T26S R3W S29 BT.

The corner falls in open field

From the same point the cor. of secs. 19, 20, 29, and 30 bears N. $88^{\circ} 54'$ W., 79.85 chs. dist., determined at record bearing and distance from the site of the original cabin on Donation Land Claim #44. The cabin site is indicated by J. C. Livingston, as per his affidavit dated August 24, 1963, attached. Nothing remains of the cabin, but the site bears N. 42° W., 450 lks. dist.

At the corner point

Set an iron pipe, $\frac{3}{4}$ ins. diam., 18 ins. long, the top 6 ins. below the surface of the ground in open field.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. $81^{\circ} 15'$ W., 277 lks. dist., with brass cap marked T26S R3W S30 RM 1963, and an arrow pointing to the corner. Reference monument falls in a N. and S. fence row and on E. edge of dirt road.

Land, rolling prairie and steep hills.

Soil, rocky clay loam.

Timber, fir, cedar, pine, hemlock, madrone, oak, maple, and dogwood; undergrowth, poison oak, timber reproduction, hazel, arrowwood, ceanothus, fern, salal, Oregon grape, blackberry, huckleberry, thistle, and bunch grass.

N. $1^{\circ} 03'$ E., bet. secs. 20 and 21.

Descend 145 ft. over NW. slope, across old logged area, through scattering timber and moderate undergrowth.

14.90 Creek, 4 lks. wide, course S. 65° W.; asc. 448 ft. over SW. slope changing to SE. slope.

18.70 Dirt road, 10 lks. wide, bears N. 30° E. and S. 30° W.

23.40 Enter heavy timber and dense undergrowth, edge bears NW. and SE.

37.14 Dirt road, 10 lks. wide, bears N. 80° W. and S. 80° E.

40.10 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, perpetuated and recorded by M. B. Germond, County Surveyor, in 1908, monumented with a sandstone, 4 x 8 x 18 ins., firmly set, protruding 6 ins. above the ground, mkd. $\frac{1}{2}$ S on W. face, from which the bearing trees marked by Germond:

A fir, 25 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ E., 109 lks. dist., with a healed blaze.

A fir, 33 ins. diam., bears N. 59° W., 83 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked