

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 26 S., R. 3 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 20 \text{ S } 21 \\ \text{T } 26 \text{ S } \text{R } 3 \text{ W} \\ 1963 \end{array}$$

Deposit the sandstone alongside the iron post.  
Corner falls in a fence line which bears E. and W.

---

From the cor. of secs. 15, 16, 21, and 22.

N.  $89^{\circ}$  38' W., bet. secs. 16 and 21.

Ascend 140 ft. through boulder-filled draw which drains E.

- 4.54 Top of rock outcropping, 36 ft. high, bears N. and S.; asc. 74 ft. over NE. slope, through scattering timber and dense undergrowth.
- 14.25 Spur, slopes NW.; desc. 43 ft. along N. slope, changing to broken NW. slope.
- 20.06 Point for the E 1/16 sec. cor. of secs. 16 and 21.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked
- $$\begin{array}{c} \text{E } 1/16 \text{ S } 16 \\ \text{S } 21 \\ 1962 \end{array}$$
- from which
- A fir, 7 ins. diam., bears N.  $19^{\circ}$  E., 61 lks. dist., mkd. E 1/16 S16 BT.
- A cedar, 19 ins. diam., bears S.  $8\frac{1}{2}^{\circ}$  W., 45 lks. dist., mkd. E 1/16 S21 BT.
- Descend 21 ft. over broken NW. slope.
- 23.46 Bottom of descent, slopes N.; asc. 23 ft. over NE. slope.
- 26.55 Top of ascent, slopes N.; desc. 90 ft. over broken NW. slope.
- 40.12 The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21 determined at record bearing and distance from the bearing trees established by Arthur Boyer, County Surveyor, during his original corner perpetuation in 1933:  
from which Boyer's bearing trees
- A cedar snag, 27 ins. diam., bears N.  $65\frac{3}{4}^{\circ}$  E., 44 lks. dist., with a healed blaze.
- A cedar, 22 ins. diam., bears S.  $70^{\circ}$  W., 22 lks. dist., with a burned center and old axe marks.
- At the corner point  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked