

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1, T. 26 S., R. 3 W.

CHAINS	
44.50	E. edge of fish pond, bears N. and S.; NE. cor. is 20 lks. N.
47.00	W. edge of fish pond, bears N. and S.; NW. cor. is 20 lks. N. Ascend 331 ft. over SE. slope.
50.90	Woven wire fence bears N. and S.
52.63	Rock Creek Road, bituminous pavement, 32 lks. wide, bears S. and NE.
59.49	From this point an iron bolt, 3/4 ins. diam., firmly set protruding 3 ins. above the ground, bears North, 0.052 chs. dist.; a woven wire fence extends N. and W. from bolt.
62.24	Spur, slopes S.; desc. 75 ft. over W. slope.
69.41	Three-wire utility line, bears NE. and SW.
79.16	The 1/4 sec. cor. of secs. 1 and 2.
	From the E 1/16 sec. cor. of secs. 1 and 12. N. 0° 36' E., on the N. and S. center line of the SE 1/4 of sec. 1. Ascend 120 ft. over broken SW. slope, through open logged area.
9.35	Enter heavy timber and moderate undergrowth, edge bears E. and W.
16.70	Spur, slopes SW.; desc. 35 ft. over NW. slope.
20.14	Point for the SE 1/16 sec. cor. of sec. 1, at the intersection with the E. and W. center line of the SE 1/4. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked SE 1/16 S 1 1963 from which A fir, 13 ins. diam., bears N. 47° E., 32 lks. dist., mkd. SE 1/16 S1 BT. A fir, 25 ins. diam., bears S. 36 1/4° W., 42 1/2 lks. dist., mkd. SE 1/16 S1 BT. Descend 157 ft. over NW. slope.
29.63	Ravine, drains W.; asc. 95 ft. over broken SW. slope.
33.65	Spur, slopes W.; desc. 73 ft. over N. slope.
40.30	The center E 1/16 sec. cor. of sec. 1.
	From the S 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. N. 87° 57' W., on the E. and W. center line of the SE 1/4 of sec. 1.