

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1, T. 26 S., R. 3 W.

CHAINS

38.56 Draw, drains S.; asc. 38 ft. over E. slope.

39.82 The N 1/16 sec. cor. of secs. 1 and 2.

Subdivision of Section 21, T. 26 S., R. 3 W.

From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.N. 0° 12' E., on the N. and S. center line of sec. 21.

Ascend 210 ft. over SE. slope, through heavy timber and light undergrowth.

5.00 Spur, slopes S. 20° W.; asc. 201 ft. over SW. slope.15.60 Same spur, slopes S. 15° E.; desc. 1 ft. over NE. slope.

20.08 Point for the center S 1/16 sec. cor. of sec. 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked
$$\begin{array}{c} C \\ S\ 1/16\ |S\ 21 \\ C \\ 1963 \end{array}$$

from which

A fir, 11 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. CS 1/16 S21 BT.A white oak, 45 ins. diam., bears N. $82\frac{1}{4}^{\circ}$ W., 200 lks. dist., mkd. CS 1/16 S21 BT.

and a local bearing tree

A white oak, 45 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ W., 243 lks. dist., mkd. PC S21 C BT on bark blaze on S. side.

Descend 1 ft. over NE. slope, across old logged area through scattering timber.

21.40 Head of draw, drains S. 85° E., asc. 95 ft. over SE. slope.26.85 Dirt road, 10 lks. wide, bears N. 80° E. and N. 60° W.28.30 Dirt road, 10 lks. wide, bears N. 65° E. and N. 75° W.28.90 Ridge, bears N. 55° E. and N. 65° W.; desc. 80 ft. over NW. slope.33.50 Enter open field, edge bears N. 50° E. and N. 55° W.

39.54 Barbed wire fence, bears E. and W.

40.16 Point for the center $\frac{1}{4}$ sec. cor. of sec. 21, at intersection with the E. and W. center line.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} C\ \frac{1}{4}\ S\ 21 \\ 1963 \end{array}$$

from which