

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21, T. 26 S., R. 3 W.

CHAINS 20.00	<p>Point for the center E 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> $\begin{array}{c} C \quad E \quad 1/16 \quad C \\ \quad \quad S \quad 21 \\ \quad \quad 1963 \end{array}$ <p>from which</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 2° W., 79 lks. dist., mkd. CE 1/16 S21 BT.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 68½° E., 87 lks. dist., mkd. CE 1/16 S21 BT.</p> <p>Descend 272 ft. over NW. slope, through light timber and undergrowth.</p>
24.74	Barbed wire fence, bears N. 25° W. and S. 25° E.
33.70	Enter field, edge bears N. and S.
39.75	Woven and barbed wire fence bears N. and S.
40.00	<p>The center ¼ sec. cor. of sec. 21.</p> <p>Descend 11 ft. over NW. slope, through scattering timber.</p>
47.25	Dirt road, and ridge bears S. 85° E. and W.; continue along ridge.
50.90	Ridge top curves to N. 80° W., enter timber, bears same; desc. 215 ft. over broken SW. slope.
57.30	Dirt road, 10 lks. wide, bears N. 15° W. and S. 15° E.
63.10	Draw, drains S.; asc. 22 ft. over SE. slope.
65.95	Ridge, bears N. 70° E. and S. 70° W., and road, 10 lks. wide, bears N. 35° E. and S. 35° W.; desc. 77 ft. along broken N. slope, along a fence.
79.31	The ¼ sec. cor. of secs. 20 and 21.
	<p>From the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 14' E., on the N. and S. center line of the SE¼ of sec. 21.</p> <p>Ascend 31 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
1.60	Spur, slopes N. 60° W.; desc. 17 ft. over NW. slope.
5.50	Draw, drains N. 80° W.; asc. 205 ft. over SW. slope.
11.70	Enter logged area, edge bears NW. and E.
15.05	Enter heavy timber, edge bears N. and SE.
17.04	Old barbed wire fence line bears N. 30° W. and S. 40° E.
20.11	<p>Point for the SE 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.</p>