

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1857 survey by Dennis Hathorn
and 1909 resurvey by Fred Mensch)

From the cor. of secs. 23, 24, 25, and 26, perpetuated by
Ben B. Irving, Douglas County Surveyor, in 1940, with a
sandstone, 17 x 8 x 8 ins., firmly set, 10 ins. in the
ground, mkd. with 2 notches on S., 1 notch on E., 5
notches on W., and 4 notches on N. edges, and a cross on
top, from which the original bearing trees:

- A rotted fir stump and fallen log, 24 ins. diam.,
bears N. 4° E., 75 lks. dist., no marks remaining.
- A rotted fir stump and fallen log, 20 ins. diam.,
bears S. 69° E., 47 lks. dist., no marks remain-
ing. (Record bearing and dist., S. 74° E., 46 lks.)
- A madrone, 20 ins. diam., bears S. 24° W., 49 lks.
dist., with blaze completely healed. (Record
bearing and dist., S. 20° W., 48 lks.)
- A sugar pine, 48 ins. diam., bears N. 33° W., 53
lks. dist., mkd. S W on partially healed and
burned blaze. (Record distance, 50 lks.)

and trees marked by Irving, in 1940:

- A fir, 37 ins. diam., bears N. 5° E., 114 lks.
dist., bark scribed T30S R2W S24 CS BT.
- A fir, 12 ins. diam., bears S. 34½° E., 65 lks.
dist., mkd. with a healed blaze.
- A fir, 8 ins. diam., bears S. 80° W., 70 lks.
dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap marked

T 30 S R 2 W
S 23 S 24
S 26 S 25
1963

Deposit the sandstone alongside the iron post.

N. 0° 11' W., bet. secs. 23 and 24, marking and blazing
the true line.

Descend 310 ft. over NE. slope, through heavy timber and
moderate undergrowth.

18.10 Creek, 2 lks. wide, course N. 25° W.; asc. 25 ft. over
SW. slope.

20.34 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap marked