

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS	
	S 1/16 S 23 S 24 T 30 S R 2 W 1963
	from which
	A fir, 9 ins. diam., bears S. $23 \frac{3}{4}^{\circ}$ E., 56 lks. dist., mkd. S 1/16 S24 BT.
	A yellow pine, 10 ins. diam., bears S. $52 \frac{1}{4}^{\circ}$ W., 19 lks. dist., mkd. S 1/16 S23 BT.
	Ascend 20 ft. over SW. slope.
22.00	Spur, slopes N. 65° W.; desc. 90 ft. over NW. slope.
29.60	Slope changes; desc. 60 ft. over steep N. slope.
30.80	Left bank of the South Fork of the Umpqua River, course West.
32.50	Right bank of river; continue over level bottom land,
35.75	Leave timber, edge bears W. and NE.; continue across grassy opening.
38.40	Left bank of a dry wash, old river channel, 6 ft. deep, drains W.
39.60	Right bank of dry wash; enter dense undergrowth.
40.64	Wire fence, bears E., and W. 4 lks. to fence corner, thence N.
40.68	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
	S 23 $\frac{1}{4}$ S 24 T 30 S R 2 W 1963
	from which
	A yellow pine, 16 ins. diam., bears N. $71 \frac{1}{2}^{\circ}$ E., 131 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	A cedar, 13 ins. diam., bears S. $6 \frac{3}{4}^{\circ}$ W., 30 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	From this point, a point established by Ben B. Irving, Douglas County Surveyor, in 1940, bears S. $36^{\circ} 17'$ W., 0.74 chs. dist., not now monumented, from which a tree marked by Irving,
	An oak, 10 ins. diam., bears N. $15 \frac{1}{2}^{\circ}$ W., 132 lks. dist., mkd. S23 CS on partially healed blaze, on the S. side of the tree.
	From this same point, a point established by James W. Byron, Deputy County Surveyor, in 1959, as a witness corner, bears N. $25^{\circ} 20'$ W., 1.02 chs. dist., monumented with with an iron post, 1 in. diam., protruding 10 ins.