

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

- 17.00 Graded and graveled road, 20 lks. wide, bears N. 10° E. and S. 10° W.
- 22.00 Spur, slopes N. 25° W.; desc. 100 ft. over broken W. slope.
- 29.80 Washed out logging road, 15 lks. wide, bears N. 40° E. and S. 15° W.; continue along N. side of old logged area.
- 36.80 Creek, 3 lks. wide, course N. 5° W.; asc. 45 ft. over NE. slope.
- 40.38 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, determined at record bearing and distance from the remaining original bearing tree,
 A fir, 31 ins. diam., bears N. 2° E., 25 lks. dist., opened to reveal the marks BT.
 At the corner point
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \text{ S } 23 \\ \frac{1}{4} \text{ S } 26 \\ \text{T } 30 \text{ S } \text{ R } 2 \text{ W} \\ 1963 \end{array}$$
 from which a new bearing tree,
 A fir, 10 ins. diam., bears S. $44\frac{1}{4}^{\circ}$ E., 151 lks. dist., mkd. $\frac{1}{4}$ S26 BT.

 S. $89^{\circ} 26'$ W., beginning new measurement.
 Ascend 3 ft. over NE. slope, through scattering timber and moderate undergrowth, along N. side of old logged area.
- 1.20 Dry wash, 4 lks. wide, drains N. 35° E.; asc. 65 lks. over NE. slope.
- 8.70 Saddle in a spur which slopes N. 25° W.; desc. 270 ft. over broken SW. slope.
- 21.90 Creek, 2 lks. wide, course N. 55° W.; enter dense undergrowth, desc. 165 ft. over broken NW. slope.
- 33.60 Left bank of the South Fork of the Umpqua River, course SW.; thence across river.
- 37.50 Right bank of river; asc. 20 ft. over SE. slope, through light timber and undergrowth.
- 39.89 The cor. of secs. 22, 23, 26, and 27, perpetuated by Ben B. Irving, Douglas County Surveyor, in 1940, with an angle iron, $1\frac{1}{2}$ ins. by $1\frac{1}{2}$ ins., 51 ins. long, firmly set 46 ins. in the ground, from which the remaining original bearing trees:
 A fir, 28 ins. diam., bears S. 33° E., 46 lks. dist., mkd. with a decayed and burned blaze.
 (Record bearing and dist., S. 28° E., 44 lks.)
 A madrone, 17 ins. diam., bears S. 15° W., 25 lks. dist., with blaze completely healed.
 and trees marked by Irving: