

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

- A fir, 32 ins. diam., bears N. 21° E., 40 lks.
dist., mkd. T30S R2W CS BT, on bark blaze.
- A fir, 12 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ E., 54 lks.
dist., mkd. with a healed blaze.
- A fir, 21 ins. diam., bears S. 58° W., 20 lks.
dist., mkd. T30S R2W S27 CS BT, on bark blaze.
- A fir, 30 ins. diam., bears N. 3° W., 38 lks.
dist., mkd. T30S R2W S22 CS BT, on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap marked

T 30 S R 2 W	
S 22	S 23
S 27	S 26
1963	

Deposit angle iron alongside the iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, pine, oak, madrone, cedar, maple, dogwood,
chinquapin, alder and yew; undergrowth, young timber,
poison oak, blackberry, salal, Oregon grape, hazel,
arrowwood, ceanothus, vine maple, willow, vines, ferns
and grasses.

N. 0° 06' E., bet. secs. 22 and 23.

Ascend 45 ft. over SE. slope, through heavy timber and
light undergrowth.

- 1.40 Leave timber, enter open field; edge bears NE. and SW.
- 1.70 From this point the SE. corner of a frame cabin, 16 ft.
by 29 ft., bears West, 27 lks. dist. Long side bears N.
and S.
- 2.00 Spur, slopes N. 80° E.; asc. 5 ft. over rolling E. slope.
- 2.20 From this point the SW. corner of a barn, 23 ft. by 27
ft., bears East, 13 lks. dist. Long side bears N. and
S.
- 7.20 Leave field; enter scattering timber and light under-
growth along top of river bank; edge bears NW. and SE.;
desc. 60 ft. over NE. slope.
- 10.80 Leave timber; enter open river bottom; edge bears N. 20°
W. and S. 20° E.; desc. 10 ft. over bottom.
- 12.60 Right bank of the South Fork of the Umpqua River, course
S. 20° E.; continue across river.
- 18.10 Left bank of river; asc. 10 ft. across river bottom.
- 20.14 Point for the S $1/16$ sec. cor. of secs. 22 and 23.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins.
in the ground, to solid rock, supported in a mound of
stone, 11 ft. base, to top, with brass cap marked