

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

## CHAINS

4.93 chs. dist., monumented with an iron post, 1 in. diam., protruding 15 ins. above ground, firmly set, with brass cap marked, County Surveyor's Office T 30 S  $\frac{1}{4}$  S 22 S 23 R 2 W 1963, and also monumented with a granite stone, 5 x 7 x 6 ins. above ground, alongside the iron post, mkd. with a cross (X) on top, from which trees mkd. by Irving, in 1940:

A fir, 17 ins. diam., bears N.  $41^{\circ}$  E., 69 lks. dist., mkd. with a healed blaze.

A fir, 15 ins. diam., bears S.  $42^{\circ}$  W., 59 lks. dist., mkd. with a healed blaze.

and a tree believed by Irving to be an original bearing tree,

A fallen and decayed oak, 10 ins. diam., bears N.  $75^{\circ}$  W., 360 lks. dist., mkd. with an open axe blaze, 6 ins. in length, at breast height.

Irving established the above point and monumented it with the granite stone, in 1940, but did not retrace the line between sections 22 and 23 and therefore had no knowledge of its relationship to existing corners to the north and south. The point is not in harmony with these corners and the oak tree he believed to be an original bearing tree was not in fact marked by Hathorn. In 1963, James W. Byron, Deputy County Surveyor, re-monumented the point with the iron post, but did no retracements to verify the position.

N.  $0^{\circ}$  02' W., beginning new measurement.

Ascend 1 ft. over SE. slope.

- 0.40 Spur, slopes E.; desc. 5 ft. over NE. slope.
- 2.00 Draw, drains S.  $80^{\circ}$  E.; asc. 160 ft. over broken SE. slope.
- 3.80 Leave prairie; enter scattering timber and moderate undergrowth; edge bears S.  $30^{\circ}$  E. and N.  $75^{\circ}$  W.
- 10.75 Dirt road, 10 lks. wide, bears N.  $85^{\circ}$  E. and S.  $85^{\circ}$  W.
- 20.20 Spur, slopes S.  $55^{\circ}$  E.; desc. 3 ft. over NE. slope.
- 20.56 Point for the N  $\frac{1}{16}$  sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

N  $\frac{1}{16}$   
S 22 | S 23  
T 30 S | R 2 W  
1963

from which

A fir, 16 ins. diam., bears N.  $19^{\circ}$  E., 93 lks. dist., mkd. N  $\frac{1}{16}$  S23 BT.

A cedar, 15 ins. diam., bears S.  $64\frac{1}{2}^{\circ}$  W., 38 lks. dist., mkd. N  $\frac{1}{16}$  S22 BT.

From this point a locally established point, by persons unknown, bears N.  $18^{\circ}$  17' E., 2.83 chs. dist., monumented with an iron pipe,  $1\frac{1}{4}$  ins. diam., protruding 9