

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS	
36.20	Old logging road, 15 lks. wide, bears N. 10° W. and S. 10° E.; slope changes; asc. 120 ft. over E. slope.
39.98	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked  $\frac{1}{4} \frac{S \ 14}{S \ 23}$ <p style="text-align: center;">T 30 S R 2 W 1963</p> from which  A fir, 38 ins. diam., bears N. 62 1/4° E., 110 lks. dist., mkd. 1/4 S14 BT.  A fir, 18 ins. diam., bears S. 39 1/2° E., 51 lks. dist., mkd. 1/4 S23 BT.  Ascend 55 ft. over E. slope.
42.00	Spur, slopes S. 5° E.; desc. 245 ft. over SW. slope.
54.60	Draw, drains S. 20° W.; asc. 75 ft. over SE. slope.
58.60	Spur, slopes S.; desc. 15 ft. over SW. slope.
59.97	Point for the W 1/16 sec. cor. of secs. 14 and 23.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked  $W \ 1/16 \ \frac{S \ 14}{S \ 23}$ <p style="text-align: center;">T 30 S R 2 W 1963</p> from which  A fir, 15 ins. diam., bears N. 29 1/4° W., 70 lks. dist., mkd. W 1/16 S14 BT.  A yellow pine, 10 ins. diam., bears S. 71 1/4° E., 44 lks. dis., mkd. W 1/16 S23 BT.  Descend 90 ft. over SW. slope.
63.70	Dirt road, 10 lks. wide, bears N. 55° W., and S. 55° E.
70.55	Wire fence, bears N. 5° W. and S. 5° E.
71.10	Dompier Creek, 15 lks. wide, dry, course SE.; enter area of the Dompier Creek Slide; asc. 90 ft. over NE. slope.
79.00	Top of ascent, pressure ridge, bears N. 10° W. and SE.; desc. 10 ft. over SW. slope.
79.96	The cor. of secs. 14, 15, 22, and 23.  Land, mountainous. Soil, rocky clay loam. Timber, fir, pine, oak, cedar, madrone, maple, dogwood, alder and yew; undergrowth, young timber, hazel, salal, arrowwood, Oregon grape, blackberry, ceanothus, huckle-