

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

berry, vines, ferns and grass.

N.  $1^{\circ}$  16' W., bet. secs. 14 and 15.

Ascend 15 ft. over broken S. slope, through medium growth timber and dense undergrowth.

5.00 Top of ascent, pressure ridge, slopes E.; desc. 40 ft. over NE. slope.

15.20 Dompier Creek, 3 lks. wide, course S.  $60^{\circ}$  E.; leave slide area, enter heavy timber and light undergrowth; asc. 25 ft. over SE. slope, along a fallen and decayed rail fence.20.335 Point for the S  $1/16$  sec. cor. of secs. 14 and 15.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

S $1/16$	
S 15	S 14
T 30 S	R 2 W
1963	

from which

A yellow pine, 6 ins. diam., bears S.  $89^{\circ}$  E., 37 lks. dist., mkd. S  $1/16$  S14 BT.A fir, 8 ins. diam., bears S.  $67\frac{1}{4}^{\circ}$  W., 18 lks. dist., mkd. S  $1/16$  S15 BT.

The old rail fence bears approximately W. and S.

Ascend 160 ft. over gradual SE. slope.

36.60 Foot of steep slope, bears E. and W.; asc. 100 ft. over S. slope.

40.67 The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, monumented with an unmarked conglomerate stone, 10 x 10 x 6 ins., loosely set 6 ins. in the ground, from which the bearing trees marked by Mensch, in 1909:Rotted wood and stump hole of a pine, bears S.  $45^{\circ}$  E., 9 lks. dist., with the pitch face of the original blaze, mkd.  $\frac{1}{4}$  S14 BT, lying beside the hold.A madrone snag, 15 ins. diam., bears S.  $49^{\circ}$  W., 32 lks. dist., mkd. S BT, and other illegible scribe marks on an opened blaze. (Record bearing, S.  $45^{\circ}$  W.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

S 15		S 14
T 30 S	R 2 W	
1963		

from which new bearing trees:

A fir, 13 ins. diam., bears S.  $19^{\circ}$  E., 36 lks.