

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

dist., mkd. $\frac{1}{4}$ S14 BT.

A fir, 19 ins. diam., bears S. 72° W., 58 lks.
dist., mkd. $\frac{1}{4}$ S15 BT.

Deposit the conglomerate stone alongside the iron post.

N. 0° 44' E., beginning new measurement.

Ascend 470 ft. over SW. slope.

14.30 Enter old logged area, edge bears SW. and S. 20° E.17.10 Dirt logging road, 15 lks. wide, bears S. 65° E., and NW., curving to N.; slope moderates; asc. 25 ft. over broken SW. slope.23.50 Spring, 2 lks. wide, course S. 40° W.; asc. 340 ft. over SW. slope.

39.98 The cor. of secs. 14 and 15, only, on the S. bdy. of sec. 10, monumented with a conglomerate stone, 15 x 12 x 8 ins., firmly set 12 ins. in the ground, mkd. with 4 notches on S. and 2 notches on E. edges, from which the remains of an original bearing tree,

A sawed yellow pine stump, 36 ins. diam., bears
S. 74° W., 28 lks. dist., with blaze face
burned out. (Mensch record dist., 27 lks.)

and a tree marked by Mensch, in 1909,

A sawed fir stump, 30 ins. diam., bears S. $47\frac{1}{2}^{\circ}$ E.,
85 lks. dist., mkd. with a well healed blaze.
(Record bearing and dist., S. $48\frac{1}{2}^{\circ}$ E., 86 lks.)

and trees marked by John H. Markham, Jr., Registered Logging Engineer, in 1959:

A fir, 10 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ E., 20 lks.
dist., with illegible scribing on an open
blaze.

A madrone, 6 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ E., 48 lks.
dist., with illegible bark scribing sloughed off.

A maple, 12 ins. diam., bears S. 55° W., 87 lks.
dist., mkd. S15 X BT, on open blaze. Reblazed
and mkd. T30S R2W S15 BT.

A fir, 8 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ W., 12 lks.
dist., with illegible scribe marks on a double
blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap marked

T 30 S R 2 W
S 10
S 15 | S 14
1963

from which a new bearing tree,