

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

chaotic tangle of boulders, downed timber, and earth and rock pinnacles.

40.55 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, restored by the method of irregular boundaries, based on Mensch's resurvey; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 15 \\ \text{ S } 22 \\ \text{ T } 30 \text{ S } \text{ R } 2 \text{ W} \\ 1963 \end{array}$$

from which

A conglomerate boulder, 29 x 15 x 9 ft. above ground, bears N. $32\frac{1}{2}^{\circ}$ W., 71 lks. dist., mkd. B X O.

A conglomerate boulder, 16 x 15 x 14 ft. above ground, bears S. $36\frac{3}{4}^{\circ}$ E., 53 lks. dist., mkd. B X O.

S. 89° 15' W., beginning new measurement.

Ascend 270 ft. over slide area and earthen bluff, general E. slope.

5.80 Western edge of Dompier Creek Slide, bears irregularly N. and S.; asc. 195 ft. over NE. slope, across old logged area, through widely scattering timber and light undergrowth.

11.80 Old logging road, 10 lks. wide, bears N. and S. 30° W.

20.15 Point for the W $\frac{1}{16}$ sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{ W } \frac{1}{16} \text{ S } 15 \\ \text{ S } 22 \\ \text{ T } 30 \text{ S } \text{ R } 2 \text{ W} \\ 1963 \end{array}$$

from which

A fir, 8 ins. diam., bears N. $3\frac{3}{4}^{\circ}$ W., 68 lks. dist., mkd. W $\frac{1}{16}$ S15 BT.

A cedar, 11 ins. diam., bears S. 51° E., 138 lks. dist., mkd. W $\frac{1}{16}$ S22 BT.

Ascend 100 ft. over NE. slope, along logging cutting line, logged to the S., standing timber to the N.

31.80 Spur, slopes SE.; asc. 45 ft. over broken SE. slope.

40.30 The cor. of secs. 15, 16, 21, and 22, monumented with a granite stone, 14 x 10 x 9 ins., firmly set 10 ins. in the ground, mkd. with 3 grooves on N. face, and a cross (X) on top, from which the remaining original bearing trees:

A sawed fir stump, 50 ins., diam., bears N. 2 E., 128 lks. dist., mkd. with a well healed blaze.