

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 4 W.

CHAINS

chinquapin, and alder; undergrowth, hazel, arrowwood, huckleberry, salal, poison oak, Oregon grape, vine maple, and dogwood.

From the cor. of secs. 20, 21, 28, and 29, determined at record distance from the remains of the original bearing trees:

A down, rotting fir, 55 ins. diam., bears N. 86° E., 263 lks. dist., marked with a decayed blaze, no scribing visible.

A rotted fir stump, 15 ins. diam., bears S. 52½° E., 46 lks. dist., no marks remaining. (Record bearing, S. 56° E.)

A fir root crown, 30 ins. diam., bears S. 34° W., 63 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

*FD. OK
2/21 M III-66*

T 22 S R 4 W
S 20 | S 21
S 29 | S 28
1963

from which new bearing trees:

A fir, 15 ins. diam., bears N. 26° E., 133 lks. dist., mkd. T22S R4W S21 BT.

A fir, 8 ins. diam., bears S. 82° E., 11 lks. dist., mkd. T22S R4W S28 BT.

A fir, 8 ins. diam., bears S. 27° W., 29 lks. dist., mkd. T22S R4W S29 BT.

A fir, 17 ins. diam., bears N. 54½° W., 47 lks. dist., mkd. T22S R4W S20 BT.

N. 0° 33' W., bet. secs. 20 and 21.

Descend 135 ft. over NE. slope, through heavy reproduction.

- 0.45 Wire fence, bears N. 30° E. and S. 30° W.
- 8.40 Dirt road, 10 lks. wide, bears N. 40° W. and S. 40° E.
- 8.50 Wire fence, bears N. 40° W. and S. 40° E.; enter field.
- 9.40 Power line, 2 cables, bears E. and W.
- 12.10 Cox Creek, 10 lks. wide, course S. 70° W.; asc. 145 ft. over S. slope.
- 16.80 Wire fence and 2 wire telephone line, bears N. 70° W. and S. 70° E.; leave field, enter moderate timber.
- 17.10 Dirt road, 35 lks. wide, bears N. 70° W. and S. 70° E.
- 17.40 Wire fence, bears N. 70° W. and S. 70° E.
- 20.01 Point for the S 1/16 sec. cor. of secs. 20 and 21.