

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 4 W.

CHAINS

N 1/16	
S 20	S 21
T 22 S R 4 W	
1963	

from which

A fir, 32 ins. diam., bears N. $34\frac{3}{4}^{\circ}$ E., 56 lks. dist., mkd. N 1/16 S21 BT.

A fir, 15 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ W., 86 lks. dist., mkd. N 1/16 S20 BT.

From this point, an aluminum pipe, 1 in. diam., established and recorded by Weyerhaeuser Timber Co., firmly set, protruding 6 ins. above ground, bears N. 31° W., 18 lks. dist.

Ascend 20 ft. over SW. slope.

23.80 Ridge, bears N. 50° W. and S. 50° E.; desc. 280 ft. over NE. slope.

39.95 The cor. of secs. 16, 17, 20 and 21, perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, with a 1 in. T-iron, firmly set, protruding 8 ins. above ground, with aluminum cap marked Wilford N. Haines, No. 239, Drain, Oregon, at record bearing and distance from the remains of the original bearing trees:

A stump hole, bears S. 62° E., 36 lks. dist.

A sawed fir stump, 60 ins. diam., bears S. 60° W., 84 lks. dist., to face, no marks remaining. (Record dist., 84 lks.)

A stump hole, bears N. $4\frac{1}{2}^{\circ}$ W., 145 lks. dist.

bearing trees mkd. by the County Surveyor in 1928:

A fir, 20 ins. diam., bears N. 60° E., 43 lks. dist., mkd. with a healed double blaze.

A fir, 36 ins. diam., bears S. 85° E., $12\frac{1}{2}$ lks. dist., mkd. T22S R4W S21 CS BT on bark blaze.

A fir snag, 42 ins. diam., bears N. 29° W., 300 lks. dist., mkd. T22S R4W CS BT on double blaze.

and a locally mkd. tree,

A fir, 14 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ W., $44\frac{1}{2}$ lks. dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 4 W	
S 17	S 16
S 20	S 21
1963	

from which a new bearing tree,

A fir, 14 ins. diam., bears N. 61° W., 84 lks. dist., mkd. T22S R4W S17 BT.