

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

N 1/16
S 8 | S 9
T 22 S | R 4 W
1963

from which

A fir, 16 ins. diam., bears S. $56\frac{3}{4}^\circ$ E., 26 lks. dist., mkd. N 1/16 S9 BT.

A fir, 15 ins. diam., bears N. 26° W., 28 lks. dist., mkd. N 1/16 S8 BT.

Ascend 145 ft. over SW. slope, along W. edge of logged area.

31.00 Ridge, bears N. 65° W. and S. 65° E.; desc. 150 ft. over NE. slope.

39.58 The cor. of secs. 4, 5, 8, and 9, remonumented with a wood post, 4 ft. long, 4 ins. square, firmly set 12 ins. in the ground, mkd. with a scribe S4 S5 S8 S9, from which the remains of the original bearing trees:

A sawed fir stump, 60 ins. diam., bears N. 38° E., 72 lks. dist., no marks remaining. (Record bearing, N. 37° E.)

A fir snag, 67 ins. diam., bears S. 80° W., 50 lks. dist., to face, no original marks remaining on old bark blaze, re-marked by County Surveyor T22S R4W S8 CS BT on bark blaze. (Record, bears S. 81° W., 47 lks. dist.)

A fir, 27 ins. diam., bears N. $46\frac{1}{2}^\circ$ W., 64 lks. dist., with illegible scribe marks on bark blaze, re-marked by County Surveyor T22S R4W S5 CS BT on double blaze.

and bearing trees mkd. by the County Surveyor:

A fir, 18 ins. diam., bears N. $34\frac{3}{4}^\circ$ E., 91 lks. dist., mkd. with a healed double blaze.

A fir, 21 ins. diam., bears S. $51\frac{3}{4}^\circ$ E., $32\frac{1}{2}$ lks. dist., mkd. with a healed double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 22 S R 4 W
S 5 | S 4
S 8 | S 9
1963

*FD. OK 9/92
M115-77
D. Peel*

from which a new bearing tree,

A fir, 12 ins. diam., bears S. $68\frac{1}{2}^\circ$ W., 64 lks. dist., mkd. T22S R4W S8 BT.

Reset the wood post alongside the iron post.