

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 4 W.

CHAINS

N. 89° 55' W., beginning new measurement.

Descend 130 ft. over NW. slope, through scattering timber and medium undergrowth.

7.60 Power line, 2 wires, bears N. 60° E. and S. 60° W.

13.20 Enter along creek; continue over nearly level bottom land.

19.30 Cox Creek, 12 lks. wide, course S., bending to SW.; asc. 95 ft. over SE. slope.

20.00 Dirt road, 20 lks. wide, bears N. and S.

24.00 Enter field, edge bears N. and S.

31.90 Woven wire fence, bears N. 75° E. and S. 75° W.

33.10 Gravelled road, 50 lks. wide, bears N. 75° E. and S. 75° W.

33.60 Enter medium timber and undergrowth, edge bears same as road.

40.20 The cor. of secs. 19, 20, 29, and 30, determined from the remains of the original bearing trees:

A sawed fir stump, 45 ins. diam., bears S. 63° E., 91 lks. dist., 100 lks. dist. on the slope, mkd. B on bark blaze. (Record distance, 100 lks.)

A fir snag, 35 ins. diam., bears S. 42° W., 86 lks. dist., mkd. 30 T22S R4W on opened blaze and BT on bark blaze. (Record bearing, S 40° W.)

A fir snag, 24 ins. diam., bears N. 73° W., 48 lks. dist., mkd. BT on bark blaze.

and a local bearing tree

A fir snag, 9 ins. diam., bears N. 60° E., 15½ lks. dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 22 S R 4 W
 S 19 | S 20
 S 30 | S 29
 1963

from which new bearing trees:

A fir, 7 ins. diam., bears N. 22½° E., 54 lks. dist., mkd. T22S R4W S20 BT.

A fir, 5 ins. diam., bears S. 33¼° E., 68 lks. dist., mkd. X BT.

A fir, 8 ins. diam., bears S. 77° W., 61 lks. dist., mkd. T22S R4W S30 BT.

A fir, 13 ins. diam., bears N. 21° W., 41 lks. dist., mkd. T22S R4W S19 BT.