

## Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 4 W.

CHAINS

in the ground, 2 ins. below the surface of the road,  
with brass cap marked

T 22 S R 4 W  
 $\frac{S 18 | S 17}{S 19 | S 20}$   
 1963

from which new bearing trees:

A fir, 27 ins. diam., bears N.  $74^{\circ}$  E., 127 lks.  
dist., mkd. T22S R4W S17 BT.

An oak, 15 ins. diam., bears S.  $57\frac{1}{4}^{\circ}$  E.,  $27\frac{1}{2}$  lks.  
dist., mkd. T22S R4W S20 BT.

An oak, 27 ins. diam., bears S.  $73^{\circ}$  W., 27 lks.  
dist., mkd. T22S R4W S19 BT.

An alder, 14 ins. diam., bears N.  $15\frac{3}{4}^{\circ}$  W., 108 lks.  
dist., mkd. T22S R4W S18 BT on bark.

From this point, a steel rod,  $\frac{5}{8}$  in. diam., firmly  
set, protruding 5 ins. above ground, bears N.  $49\frac{1}{2}^{\circ}$  W.,  
4 lks. dist.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, madrone, alder, oak, and maple;  
undergrowth, young timber, hazel, arrowwood, live oak,  
huckleberry, salal, poison oak, Oregon grape, ferns,  
and vines.

From the cor. of secs. 16, 17, 20, and 21.

S.  $89^{\circ} 44'$  W., bet. secs. 17 and 20.

Ascend 40 ft. over NE. slope, changing to broken N.  
slope, through heavy timber and medium undergrowth.

8.30 Top of ascent; desc. 5 ft. along N. slope.

19.965 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap marked

E  $\frac{1}{16}$   $\frac{S 17}{S 20}$   
 T 22 S R 4 W  
 1963

from which

A fir, 7 ins. diam., bears N.  $41^{\circ}$  W., 25 lks.  
dist., mkd. E  $\frac{1}{16}$  S17 BT.

A fir, 7 ins. diam., bears S.  $28^{\circ}$  W., 20 lks.  
dist., mkd. E  $\frac{1}{16}$  S20 BT.

Descend 100 ft. over NW. slope.

21.70 Old fence, bears N. and S.

34.20 High tension power line, 3 cables, bears N.  $5^{\circ}$  W. and  
S.  $5^{\circ}$  E.

38.60 Woven wire fence, bears N. and S.