

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

1 in. T iron, firmly set, protruding 8 ins. above the ground, from which the remains of the original bearing trees:

A sawed fir stump, 28 ins. diam., bears N. 48° E., 5 lks. dist., 3 lks. dist. to face, no marks remaining on opened face. (Record distance, 3 lks.)

A sawed fir stump, 22 ins. diam., bears S. 35° E., 24½ lks. dist., 23 lks. dist. to face, mkd. T22S BT on opened and burned double blaze. (Record distance, 23 lks.)

A sawed fir stump, 27 ins. diam., bears N. 45° W., 20 lks. dist., 18 lks. dist. to face, no marks visible on opened face. (Record distance, 18 lks.)

and bearing trees by Haines

A fir, 18 ins. diam., bears N. 55½° E., 30 lks. dist., mkd. S26 T22S R6W BT.

A fir, 20 ins. diam., bears S. 9° E., 99 lks. dist., mkd. S35 T22S R6W BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap marked

T 22 S R 6 W
S 34 | S 26
 | S 35
1963

*Fd BC 8/10
M 110-47
FO. B. C. 6/92
J. BRANCH
M 115-26*

Reset the T iron alongside iron post.

N. 0° 15' W., along the W. bdy. of sec. 26, marking and blazing the true line.

Descend 75 ft. over N. slope, through heavy timber and moderate undergrowth.

3.80 The closing corner of secs. 27 and 34, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, monumented with a 1 in. T iron, firmly set, protruding 10 ins. above the ground, from which the remains of the original bearing trees:

A down fir, 24 ins. diam., bears S. 36° W., 25 lks. dist., with no marks visible.

A down fir stump, 34 ins. diam., bears N. 30° W., 39 lks. dist., marked S R6W S27 on opened face.

and bearing trees by Haines

A fir, 6 ins. diam., bears S. 80° W., 25½ lks. dist., mkd. CC S34 T22 R6 BT.

A fir, 6 ins. diam., bears N. 78° W., 34½ lks. dist., mkd. S27 T22 R6 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked