

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

T 22 S R 6 W			
C S 27	S 26		
C S 34	S 26		
1963			

fd B.C. 8/20
" 10-41

Reset the T iron alongside iron post.

Descend 240 ft. over N. slope, through heavy timber and light undergrowth.

- 13.60 Lost Cabin Creek, 10 lks. wide, course S. 60° E.; asc. 260 ft. over S. slope.
- 20.20 Enter W. edge of logged area, edge bears N. and E.
- 30.60 Spur, slopes SW.; desc. 10 ft. over NW. slope.
- 35.80 Draw, drains W.; asc. 50 ft. over S. slope.
- 39.78 The $\frac{1}{4}$ sec. cor. of sec. 26 only, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, monumented with a 1 in. T iron, firmly set, protruding 10 ins. above the ground, from which the remains of the original bearing tree:

A cedar, 72 ins. diam., bears N. 40° E., 30 lks. dist., the original marks I could not find. It has been remarked $\frac{1}{4}$ S BT, approximately 30 years ago according to the growth rings on the overgrowth. (Record calls for a Redwood)

and one local tree

A madrone, 11 ins. diam., bears N. 55 $\frac{1}{2}$ ° W., 25 lks. dist., marked $\frac{1}{4}$ S BT, this was apparently marked at the same time the original NE. tree was remarked.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked

T 22 S R 6 W			
	S $\frac{1}{4}$ 26		
1963			

from which one new bearing tree

A fir, 14 ins. diam., bears S. 63 $\frac{1}{2}$ ° E., 48 lks. dist., mkd. $\frac{1}{4}$ S 26 BT.

Reset the T iron alongside iron post.

N. 0° 16' E., beginning new measurement.

Ascend 10 ft. over S. slope.

- 1.30 Spur, slopes W.; desc. 10 ft. over N. slope.
- 1.92 Point for the $\frac{1}{4}$ sec. cor. of sec. 27 only, at midpoint latitudinally on the E. bdy. of sec. 27.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked