

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

S  $27\frac{1}{4}$  |

T 22 S R 6 W  
1963

from which

A fir, 15 ins. diam., bears S.  $20\frac{1}{2}^\circ$  W., 55 lks. dist., mkd.  $\frac{1}{4}$  S27 BT.

A cedar, 27 ins. diam., bears N.  $63^\circ$  W., 167 lks. dist., mkd.  $\frac{1}{4}$  S27 BT.

Descend 30 ft. over NW. slope.

- 4.60 Draw, drains W.; asc. 115 ft. over broken SW. slope.
- 20.00 Creek, 3 lks. wide, course S.  $5^\circ$  W.; asc. 55 ft. along creek bottom.
- 25.30 Leave same creek, course S. from N.  $30^\circ$  E., asc. 215 ft. over SW. slope.
- 39.82 The cor. of secs. 22, 23, 26, and 27, monumented with a 1 in. T iron, firmly set, marked Wilford N. Haines, No. 239, Drain, Oregon, recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, from which the remains of the original bearing trees:

A sawed fir stump, 52 ins. diam., bears S.  $58^\circ$  E., 54 lks. dist., marked with a healed blaze. (Record calls for a Redwood.)

A down fir, 24 ins. diam., bears S.  $40^\circ$  W., 2 lks. dist., marked with a healed blaze.

A down fir, 20 ins. diam., bears N.  $22^\circ$  W., 15 lks. dist., marked 22W on opened blaze and remarked T22S R6W S22 on bark blaze.

and the County Surveyor's bearing trees

A fir, 10 ins. diam., bears N.  $29^\circ$  E., 38 lks. dist., mkd. T22S R6W S23 CS BT on double blaze.

A fir, 10 ins. diam., bears S.  $39\frac{1}{2}^\circ$  W., 33 lks. dist., mkd. T22S R6W S27 CS BT on double blaze.

A fir, 12 ins. diam., bears N.  $55\frac{1}{2}^\circ$  W., 15 lks. dist., mkd. T22S R6W S22 CS BT on double blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 6 W  
S 22 | S 23  
S 27 | S 26  
1963

from which a new bearing tree

A fir, 8 ins. diam., bears S.  $77^\circ$  E., 174 lks. dist., mkd. T22S R6W S26 BT.

Reset the T iron alongside the iron post.