

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

Land, mountainous.
Soil, rocky clay and loam.
Timber, fir, cedar, madrone, hemlock, maple, dogwood,
yew, and chinquapin; undergrowth, hazel, salal, poison
oak, Oregon grape, vine maple and ferns.

From the cor. of secs. 14, 15, 22, and 23, monumented
with a 1 in. T iron, firmly set, protruding 10 ins.
above the ground, mkd. Wilford N. Haines, No. 239,
Drain, Oregon, from which the remaining original bearing
trees:

A fir, 36 ins. diam., bears N. $43\frac{3}{4}^{\circ}$ E., 31 lks.
dist., no marks remaining on opened and rotted
face. (Record bearing, N. 36° E.)

A fir, 67 ins. diam., bears S. 77° E., 103 lks.
dist., no marks remaining, this tree was opened
before I located the cor. (Record bearing,
S. 71° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap marked

T 22 S R 6 W
S 15 S 14
S 22 S 23

1963

from which new bearing trees

A cedar, 11 ins. diam., bears N. $59\frac{1}{4}^{\circ}$ E., 61 lks.
dist., mkd. T22S R6W S14 BT.

A fir, 13 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., 81 lks.
dist., mkd. T22S R6W S23 BT.

A fir, 6 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ W., 51 lks.
dist., mkd. T22S R6W S22 BT.

A fir, 15 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ W., 81 lks.
dist., mkd. T22S R6W S15 BT.

Reset the T iron alongside iron post.

N. $0^{\circ} 07'$ W., bet. secs. 14 and 15.

Ascend 10 ft. over SE. slope.

- 1.40 Top of ascent, slopes E.; desc. 85 ft. along E. slope,
changing to NE. slope.
- 20.50 Spur, slopes N. 40° E.; desc. 200 ft. over NW. slope.
- 27.90 Creek, 1 lk. wide, course S. 60° W.; asc. 115 ft. over
SE. slope.
- 32.20 Spur, slopes N. 80° W.; desc. 175 ft. over N. slope.
- 39.22 The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, perpetuated and
recorded by Ben B. Irving, Deputy County Surveyor, in
1928, from the original bearing trees, which are no
longer in existence, monumented with a sandstone, 14 x
8 x 6 ins., mkd. $\frac{1}{4}$ on E. face, firmly set 8 ins. in the
ground. In 1958 Wilford N. Haines, Registered Land Sur-
veyor, No. 239, set a 1 in. T iron, 36 ins. long, 24
ins. in the ground alongside the sandstone.