


Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which new bearing trees

A hemlock, 10 ins. diam., bears S. 56° E., 24 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

A hemlock, 10 ins. diam., bears S. 30° W., 44½ lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Reset the T iron and deposit stone alongside iron post.

N. 0° 04' E., beginning new measurement.

Descend 55 ft. over N. slope.

- 1.45 S. bank of Elk Creek, 110 lks. wide, course N. 60° W.
- 2.75 N. bank of Elk Creek; asc. 265 ft. over S. slope.
- 3.90 Barbed wire fence, 4 strands, bears N. 50° W. and S. 50° E.; enter open field.
- 29.35 State highway No. 38, 47 lks. wide, bears N. 70° W. and S. 70° E.
- 29.85 Woven wire fence bears N. 70° W. and S. 70° E.
- 40.49 The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1928, monumented with a water pipe, 2½" diam., protruding 8" above ground, from which the remains of the original NE. bearing tree:

A sawed oak stump, 43 ins. diam., bears N. 30° E., 270 lks. dist., 267 lks. dist. to the face, S in negative or overgrowth lying alongside the stump. (Record distance, 267 lks.)


and bearing trees by B. Irving in 1928

An oak, 36 ins. diam., bears N. 14¾° E., 353 lks. dist., mkd. with a healed blaze.

An oak, 35 ins. diam., bears S. 65¼° W., 138 lks. dist., mkd. S15 T22 R6 CS on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked



*Fd. OK
M109-74
J. BEANEN
3/90*