

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

W 1/16 $\frac{S\ 15}{S\ 22}$
T 22 S R 6 W
1963

from which

A fir, 28 ins. diam., bears N. $70\frac{1}{2}^\circ$ E. 120 lks.
dist., mkd. W 1/16 S15 BT.

A fir, 16 ins. diam., bears S. $56\frac{1}{4}^\circ$ E., 252 lks.
dist., mkd. W 1/16 S22 BT.

Ascend 255 ft. over NE. slope, changing to E. slope.

75.30 Spur, slopes N. 5° W.; desc. 166 ft. over W. slope.

80.05 Dirt road, 20 lks. wide, bears NE. and SW.

80.84 The cor. of secs. 15, 16, 21, and 22.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, madrone, chinquapin,
dogwood, yew alder, willow, and oak; undergrowth, young
timber, hazel, arrowwood, huckleberry, salal, poison
oak, Oregon grape, vine maple, ferns and vines.

N. $0^\circ 20'$ W., bet. secs. 15 and 16.

Descend 330 ft. over NW. slope, changing to N. slope,
through heavy timber and moderate undergrowth.

13.90 Woven wire fence and S. edge of field, bears E. and W.

19.925 Point for the S 1/16 sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., the top
18 ins. below the surface of the ground, in plowed
field, with brass cap marked

S 1/16
S 16 | S 15
T 22 S R 6 W
1963

from which

A fir, 15 ins. diam., bears N. $87\frac{1}{2}^\circ$ E., 325 lks.
dist., mkd. S 1/16 S15 BT.

An oak, 15 ins. diam., bears S. 68° E., 378 lks.
dist., mkd. S 1/16 S15 BT.

No suitable bearing trees available within limits
in sec. 16.

Descend 35 ft. over gentle N. slope.

31.00 Enter timber, edge bears SE. and NW.

37.86 The witness corner of the $\frac{1}{4}$ sec. cor. of secs. 15 and
16, established and recorded by Milo E. Godfrey, Deputy
County Surveyor, in 1961, monumented with an iron post,
 $1\frac{1}{2}$ ins. diam., protruding 14 ins. above the ground,
with brass cap marked