

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

## COUNTY SURVEYORS OFFICE

 $\frac{1}{4}$  S 16 | S 15

W. C. N.

131.5 FT. TO COR.

1961

from which bearing trees by Godfrey

A fir, 8 ins. diam., bears S.  $18\frac{1}{4}^{\circ}$  E.,  $27\frac{1}{2}$  lks. dist., mkd. WC  $\frac{1}{4}$  S15 CS BT on double blaze.

A fir, 13 ins. diam., bears S.  $37\frac{1}{4}^{\circ}$  W.,  $10\frac{1}{2}$  lks. dist., mkd. with a partially healed double blaze.

This witness corner was established by the County Surveyor's Office when the witness corner point established in 1928, by B. Irving, was obliterated by a logging road.

Descend 5 ft. over N. slope.

- 38.29 The witness corner of the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, established and recorded by Ben B. Irving, Deputy County Surveyor, in 1928, determined from the remains of Irving's 1928 bearing trees

A stump hole, bears S.  $29\frac{3}{4}^{\circ}$  E., 60 lks. dist.

A sawed fir stump, 36 ins. diam., bears S.  $78\frac{1}{4}^{\circ}$  W., 216 lks. dist., mkd. S C on burned face.

This point falls in a dirt road, 20 lks. wide, bears N.  $65^{\circ}$  W., and S.  $65^{\circ}$  E.

Descend 25 ft. over N. slope.

- 39.85 True point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, determined at record bearing and distance for the County Surveyor's 1928 witness corner. The true point falls in Elk Creek, 155 lks. wide, course N.  $65^{\circ}$  W., where it is impracticable to establish a permanent monument.

N.  $0^{\circ} 10'$  W., beginning new measurement.

Ascend 50 ft. over gentle S. slope, through open pasture.

- 4.05 Woven wire fence, bears E. and W.
- 29.55 State Highway No. 38, 47 lks. wide, bears N.  $80^{\circ}$  E. and S.  $80^{\circ}$  W.
- 40.00 The cor. of secs. 9, 10, 15, and 16 monumented with an old wooden post, 4 ins. sq., 3 ft. long, lying in a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, at intersection of old fence lines extending S. and W.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 6 W

S 9 | S 10

S 16 | S 15

1963