

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 6 W.

CHAINS

and bearing trees by Godfrey.

A fir, 7 ins. diam., bears N. 50° E., 74 lks.
dist., mkd. with partially healed double blaze.

A fir, 8 ins. diam., bears S. 21 $\frac{3}{4}$ ° E., 31 lks.
dist., mkd. with partially healed double blaze.

A hemlock, 10 ins. diam., bears S. 16° W., 69 lks.
dist., mkd. T22S R6W S20 CS BT on double blaze.

A chinquapin, 9 ins. diam., bears N. 10 $\frac{1}{2}$ ° W.,
39 lks. dist., mkd. T22S R6W S17 CS BT on
double blaze.

From this point, an iron post, 1 $\frac{1}{2}$ ins. diam., protruding
10 ins. above the ground, bears W., 4 lks. dist., with
brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S R 6 W

S 17 | S 16

S 20 | S 21

1961

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, dogwood, ash, alder, yew,
maple, madrone, chinquapin and willow; undergrowth,
young timber, hazel, arrowwood, manzanita, huckleberry,
salal, poison oak, Oregon grape, vine maple, ferns and
vines.

Subdivision of Sec. 15, T. 22 S., R. 6 W.

The following subdivision of section 15 was exe-
cuted in conformity with legal surveying practice. The
record of true line notes, only, is set forth in the
following field notes.

From the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

N. 0° 01' W., on the N. and S. center line of sec. 15.

Descend 160 ft. along W. slope, changing to NW. slope,
through heavy timber and moderate undergrowth.

5.00 Draw, drains W.; asc. 130 ft. over SW. slope.

17.00 Spur, slopes N. 35° W.; desc. 70 ft. over NE. slope.

19.765 Point for the center S 1/16 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap marked

C

S 1/16 | S 15

C

1963

from which

A fir, 20 ins. diam., bears N. 55 $\frac{3}{4}$ ° E., 30 $\frac{1}{2}$ lks.
dist., mkd. CS 1/16 S15 BT.