

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 15, T. 22 S., R. 6 W.

CHAINS	
	<p>A fir, 15 ins. diam., bears N. 47° W., 62½ lks. dist., mkd. CS 1/16 S15 BT.</p> <p>Descend 220 ft. over N. slope, enter scattered reproduction, edge bears N. 10° W. and S. 35° E.</p>
27.70	Draw, drains NW.; desc. 110 ft. over NW. slope.
39.53	Point for the center ¼ sec. cor. of sec. 15, at the intersection of the E. and W. center line.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">C ¼ S 15 1963</p> <p>from which</p> <p>A fir, 8 ins. diam., bears S. 1¼° E., 11 lks. dist., mkd. C ¼ S15 BT.</p> <p>A fir, 9 ins. diam., bears N. 57° W., 41 lks. dist., mkd. C ¼ S15 BT.</p> <p>Descend 35 ft. over broken NW. slope.</p>
43.00	Draw, drains NW.; desc. 95 ft. over broken NW. slope.
47.45	Enter pasture, edge bears E. and W.
53.90	Elk Creek, 70 lks. wide, course N. 65° W.; continue across level bottom land.
62.00	Same creek, course SE. from N.; continue along creek bed.
70.00	Leave Elk Creek, course S. from NE.; asc. 15 ft. over gentle S. slope.
78.70	State Highway No. 38, 47 lks. wide, bears N. 70° E., curving E., and S. 70° W.
79.74	The ¼ sec. cor. of secs. 10 and 15.
	<p>From the ¼ sec. cor. of secs. 14 and 15.</p> <p>N. 89° 37' W., on the E. and W. center line of sec. 15.</p> <p>Ascend 70 ft. along broken N. slope, through light timber and undergrowth.</p>
13.50	Spur, slopes N.; desc. 90 ft. over NW. slope.
19.70	Creek, 3 lks. wide, course N. 10° E.; asc. 135 ft. over E. slope
29.80	Spur, slopes N.; desc. 55 ft. over broken W. slope.
40.42	The center ¼ sec. cor. of sec. 15.
	Descend 130 ft. over W. slope.
50.40	Dirt road, 15 lks. wide, bears NE. and SW.
50.85	Woven wire fence, edge of pasture, bears NE. and SW.
54.25	Enter scattering timber, edge bears NW. and SE.