

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 4 W.

CHAINS	
12.40	Spur, slopes SW.; desc. 530 ft. over SW. slope.
29.85	Draw, drains W.; desc. 30 ft. down draw.
31.50	Leave draw, drains S. 85° W.; desc. 140 ft. over SW. slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S } 25 \\ \text{S } 36 \\ \text{T } 24 \text{ S } \text{ R } 4 \text{ W} \\ 1963 \end{array}$ from which A cedar, 18 ins. diam., bears N. 20° W., 21 lks. dist., mkd. $\frac{1}{4}$ S25 BT. A fir, 8 ins. diam., bears S. 36° W., 42 lks. dist., mkd. $\frac{1}{4}$ S36 BT. Descend 25 ft. over SW. slope.
40.44	Barbed wire fence, bears N. and S.
41.40	Slope changes; desc. 135 ft. over NW. slope.
52.25	Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.
52.85	Cantell Creek, 3 lks. wide, course S. 35° W.; asc. 245 ft. over SE. slope.
60.03	Point for the W $\frac{1}{16}$ sec. cor. of secs. 25 and 36. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{W } \frac{1}{16} \text{ S } 25 \\ \text{S } 36 \\ \text{T } 24 \text{ S } \text{ R } 4 \text{ W} \\ 1963 \end{array}$ from which A fir, 27 ins. diam., bears N. $78\frac{1}{2}$ ° W., 9 lks. dist., mkd. W $\frac{1}{16}$ S25 BT. A fir, 14 ins. diam., bears S. $31\frac{3}{4}$ ° E., 28 lks. dist., mkd. W $\frac{1}{16}$ S36 BT. Ascend 60 ft. over SE. slope.
64.50	Spur, slopes S. 40° W.; desc. 205 ft. over NW. slope, through scattering timber and light undergrowth.
72.80	Small spring in a draw, drains S. 50° W.; desc. 85 ft. over SW. slope.
75.00	Old logging road, 10 lks. wide, bears N. 85° E. and S. 85° W.
80.04	The cor. of secs. 25, 26, 35, and 36, monumented by