

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 4 W.

CHAINS

Milo Godfrey, Deputy County Surveyor in 1963 with a steel truck axle,  $1\frac{1}{2}$  ins. diam., protruding 12 ins. above ground, firmly set, with steel flange, 6 ins. diam., on top mkd.

	T 24 S	
S 26		S 25
S 35		S 36
R	4 W	
	1963	

from which the remaining original bearing trees:

A white oak, 20 ins. diam., bears N.  $18\frac{1}{4}^{\circ}$  E., 111 lks. dist., lying face down with no marks visible. (Record, bears N.  $17^{\circ}$  E., 114 lks. dist.)

A fir stump, 50 ins. diam., bears S.  $59\frac{1}{2}^{\circ}$  W., 118 lks. dist., with a portion of the tree lying on the ground, mkd. 24 RW. on an open blaze. (Record, bears S.  $59^{\circ}$  W., 117 lks. dist.)

An oak, 13 ins. diam., bears N.  $5\frac{1}{4}^{\circ}$  W., 69 lks. dist., lying face down with rotted blaze. (Record bearing, N.  $7^{\circ}$  W.)

and bearing trees mkd. by Godfrey in 1963:

A white oak, 14 ins. diam., bears N.  $68\frac{3}{4}^{\circ}$  E., 32 lks. dist., mkd. T24S R4W S25 CS BT.

A white oak, 13 ins. diam., bears S.  $64\frac{1}{4}^{\circ}$  E., 37 lks. dist., mkd. T24S R4W S36 CS BT.

A white oak, 12 ins. diam., bears S.  $23\frac{1}{2}^{\circ}$  W., 63 lks. dist., mkd. T24S R4W S35 CS BT.

A fir, 6 ins. diam., bears N.  $50\frac{3}{4}^{\circ}$  W., 48 lks. dist., mkd. T24S R4W S26 CS BT.

Add the marks BLM to the top of the steel plate.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, oak, madrone, hemlock, dogwood, ash, yew, and alder; undergrowth, young timber, hazel, ceanothus, arrowwood, manzanita, live oak, huckleberry, salal, poison oak, Oregon grape, vines, ferns, weeds, and grasses.

N.  $0^{\circ} 31'$  E., bet. secs. 25 and 26.

Ascend 55 ft. over SW. slope, through scattering timber and light undergrowth.

4.70 A spur, slopes S.  $25^{\circ}$  W.; asc. 190 ft. over open SW. slope.

19.99 Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

	S 1/16	
S 26		S 25
T 24S		R 4 W
	1963	