

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 4 W.

CHAINS

At the corner point

Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
S 23 S 24
S 26 S 25
1963

from which new bearing trees:

A cedar, 17 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. T24S R4W S24 BT.A fir, 10 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ E., 123 lks. dist., mkd. T24S R4W S25 BT.A fir, 16 ins. diam., bears S. $61\frac{3}{4}^{\circ}$ W., 121 lks. dist., mkd. T24S R4W S26 BT.A fir, 21 ins. diam., bears N. $39\frac{1}{4}^{\circ}$ W., 72 lks. dist., mkd. T24S R4W S23 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, oak, madrone, hemlock, dogwood, ash, yew, and alder; undergrowth, young timber, hazel, ceanothus, arrowwood, manzanita, live oak, huckleberry, salal, poison oak, Oregon grape, vines, ferns, weeds, and grasses.

(Restoring the 1896 survey by Oscar F. Thiel)

S. $89^{\circ} 44'$ E., between secs. 24 and 25.

Ascend 75 ft. over SW. slope, through moderate timber and light undergrowth.

- 3.60 Spur, slopes N. 40° W.; desc. 10 ft. over NE. slope, through heavy timber and dense undergrowth.
- 5.70 Slope changes; desc. 115 ft. over SE. slope.
- 11.00 Slope changes; desc. 135 ft. over NE. slope.
- 19.70 Creek, 1 lk. wide, course N.; desc. 2 ft. over NE. slope
- 21.50 Creek, 2 lks. wide, course N. 25° E.; asc. 15 ft. over NW. slope.
- 24.35 Creek, 1 lk. wide, course N. 10° W.; asc. 250 ft. over general NW. slope.
- 35.60 Spur, slopes N. 45° E.; descend 25 ft. over NE. slope.
- 37.70 Slope changes; desc. 85 ft. over SE. slope.
- 39.65 The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, remonumented by Milo Godfrey, Deputy County Surveyor, in 1963, with an iron post, 1 in. diam., protruding 2 ins. above ground, firmly set, with brass cap mkd.

T 24 S
$\frac{1}{4}$ S 24
S 25
R 4 W
1963