


County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25, T. 24 S., R. 4 W.

CHAINS	
2.12	Jeffers Creek, 3 lks. wide, course S. 5° E.; asc. 310 ft. over NE. slope.
20.60	Spur, slopes N. 30° E.; desc. 265 ft. over NW. slope.
29.55	Cantell Creek, 1 lk. wide, course S. 25° W.; asc. 265 ft. over SE. slope.
39.70	Spur, slopes S. 20° E.; desc. 5 ft. over SW. slope.
40.10	The center $\frac{1}{4}$ sec. cor. of sec. 25. Descend 35 ft. over SW. slope, through scattering timber and dense undergrowth.
44.75	Draw, drains S. 10° E.; asc. 335 ft. over SE. slope.
57.50	Ridge, bears N. 45° E. and S. 45° W.; desc. 10 ft. along N. slope.
60.02	Point for the center W 1/16 sec. cor. of sec. 25. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16  S 25 1963 </div> from which A forked fir, 30 ins. diam., bears S. $18\frac{3}{4}$ ° W., 40 lks. dist., mkd. CW 1/16 S25 BT. A fir, 26 ins. diam., bears West, 9 lks. dist. mkd. CW 1/16 S25 BT. Descend 280 ft. over NW. slope, through heavy timber and dense undergrowth.
74.70	Spur, slopes N. 40° W.; desc. 200 ft. over NW. slope.
79.94	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
	From the W 1/16 sec. cor. of secs. 25 and 36. N. 0° 20' E., on the N. and S. center line of the SW. $\frac{1}{4}$ of sec. 25. Descend 130 ft. over SE. slope, through scattering timber and undergrowth.
9.50	Spur, slopes S. 25° W.; asc. 130 ft. over broken SW. slope.
19.90	Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the SW $\frac{1}{4}$. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> SW 1/16 S 25 1963 </div> from which