

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25, T. 24 S., R. 4 W.

CHAINS

A fir, 24 ins. diam., bears N. 29° W., 53 lks. dist., mkd. SW 1/16 S25 BT.

A cedar, 25 ins. diam., bears S. 20° E.; 10 lks. dist., mkd. SW 1/16 S25 BT.

Ascend 445 ft. over broken SW. slope, through medium timber and dense undergrowth.

19.93 Woven wire fence, bears E. and W.

38.30 Summit of W. butte; ridge bears NE. and SW.; desc. 40 ft. over N. slope.

39.80 The center W 1/16 sec. cor. of sec. 25.

From the center S 1/16 sec. cor. of sec. 25.

S. 89° 31' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 25.

Ascend 5 ft. over SE. slope, through scattering timber and light undergrowth.

1.80 Creek, 3 lks. wide, course S. 15° E.; asc. 380 ft. over broken SE. slope.

16.80 Spur, slopes S. 20° W.; enter along woven wire fence; desc. 20 ft. over SW. slope.

19.98 The SW 1/16 sec. cor. of sec. 25.

Descend 25 ft. over SW. slope.

23.65 Draw, drains S.; asc. 40 ft. over SE. slope.

30.00 Spur, slopes S.; desc. 225 ft. over SW. slope.

39.96 The S 1/16 sec. cor. of secs. 25 and 26.

Remonumentation of Certain Original Corners in T. 24 S.,
R. 4 W., Willamette Meridian, Oregon

The following field notes describe remonumentations of original corners in T. 24 S., R. 4 W., as provided for in general special instructions for Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

(Remonumenting corners established by Gordon and Gardner in 1855)

The cor. of secs. 14, 15, 22, and 23 is determined by chaining on approximate record bearings from known corners to the north and west, and pinpointed at record distance from the stump hole of each of the original bearing trees:

Oak stump hole, bears N. 4° E., 634 lks. dist.

Oak stump hole, bears S. 11° E., 233 lks. dist.
(Record bearing, S. 13° E.)

Oak stump hole, bears S. 69° W., 148 lks. dist.
(Record bearing, S. 75° W.)