

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 23 S., R. 7 W.

CHAINS

and bearing tree by James W. Byron, in 1960

A white oak, 10 ins. diam., bears S. 34° W.,
44 lks. dist., mkd. $\frac{1}{4}$ S32 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.FD OK 4-92
DOLAN M 115-3

T 23 S R 7 W

 $\frac{1}{4}$ S 32
1963Deposit $\frac{3}{4}$ in. iron pipe alongside iron post.

S. 89° 46' W., beginning new measurement.

Ascend 50 ft. over E. slope, through open prairie.

2.25 Board fence, bears S. and E.

2.66 Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, at midpoint
longitudinally on the N. bdy. of sec. 5, T. 24 S.,
R. 7 W.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.FD OK 4-92
DOLAN M 115-3 $\frac{1}{4}$ S 5
T 24 S R 7 W
1963

from which

A fir, 9 ins. diam., bears S. 45° E., 110 lks.
dist., mkd. $\frac{1}{4}$ S 5 BT.No other suitable bearing tree available within
limits.

Ascend 105 ft. over E. slope.

5.60 Dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.

11.30 Spur, slopes S. 20° E., fence bears N. 20° W. and S.
20° E., enter timber, edge bears same as fence; desc.
105 ft. over SW. slope.18.95 Creek, 2 lks. wide, course S.; asc. 35 ft. over SE.
slope.22.88 Point for the W 1/16 sec. cor. of sec. 5 only, T. 24 S.,
R. 7 W.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins.
in the ground, with brass cap mkd. $\frac{1}{16}$ W 1/16 S 5
T 24 S R 7 W
1963

from which

A fir, 14 ins. diam., bears S. 60 $\frac{1}{2}$ ° E., 142 lks.
dist., mkd. W 1/16 S5 BT.Fd. by:
Don BENTZ
3/83
M 90-38 A/B