

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 23 S., R. 7 W.

CHAINS

from which the remains of the original SE. bearing tree

A stump hole with pieces of burned fir stump,
bears S. 12° E., 26 lks. dist.

and bearing trees by Godfrey

A fir, 18 ins. diam., bears S. 20° E., 17 lks.
dist., mkd. T24S R7W CC S5 CS BT.

A fir, 14 ins. diam., bears S. 39° W., 125 lks.
dist., mkd. T24S R7W CC S6 CS BT.

Descend 45 ft. over W. slope.

8.25 Creek, 3 lks. wide, course S.; asc. 140 ft. over E.
slope.

14.20 Spur, slopes S.; desc. 40 ft. over W. slope, changing
to SW. slope.

19.90 Creek, 1 lk. wide, course S. 20° E.; asc. 130 ft. over
E. slope.

32.90 Spur, slopes S.; desc. 30 ft. over W. slope.

39.90 Draw, drains S.; asc. 5 ft. over E. slope.

40.22 Point for the $\frac{1}{4}$ sec. cor. of sec. 31 only, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 23 S R 7 W

 S 31
 1963

from which

A fir, 16 ins. diam., bears N. 43° E., $60\frac{1}{2}$ lks.
dist., mkd. X at breast height and BT at base
of tree.

A fir, 10 ins. diam., bears N. 53° W., 95 lks.
dist., mkd. $\frac{1}{4}$ S31 BT.

Ascend 95 ft. over E. slope.

48.40 Spur, slopes S.; desc. 50 ft. over W. slope.

52.90 Draw, drains S.; asc. 90 ft. over E. slope.

62.50 Ridge, bears N. 55° E. and S. 55° W.; asc. 130 ft.
along N. slope.

80.44 The corner of Tps. 23 S., Rs. 7 and 8 W., on the N.
bdy. of T. 24 S., R. 7 W., perpetuated and recorded
by Deputy County Surveyor, James W. Byron, in 1960,
monumented with an iron post, 1 in. diam., protruding
12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R T 23 S R
8 S 36 | S 31 7
W T 24 S W
 1960

Fd. by:
Don BENT
3/83
M 90-38 A+B