

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 23 S., R. 7 W.

CHAINS

from which the remains of the original bearing trees

A rotted fir stump, 20 ins. diam., bears N. 80° E., 7 lks. dist., no marks remaining.

A fir snag, 35 ins. diam., bears S. 65° W., 59 lks. dist., mkd. T24 S1 on opened face.

A fir, 33 ins. diam., bears N. 29° W., 115 lks. dist., with a healed blaze. (Record, N. 28° W., 110 lks. dist.)

and a bearing tree mkd. by Byron

A fir, 20 ins. diam., bears N. 72° E., 95 lks. dist., with a partially healed double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, chinquapin, maple, madrone, and yew; undergrowth, salal, hazel, poison oak, huckleberry, vine maple, grape, blackberry, ferns and vines.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1857 survey by Dennis Hathorn and the retracement by Williams R. Whipple in 1893)

Point for the cor. of secs. 4, 5, 8 and 9, determined at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 7 W
S 5 S 4
S 8 S 9
1963

from which

A fir, 10 ins. diam., bears N. 44½° E., 154 lks. dist., mkd. T24S R7W S4 BT.

A locust, 17 ins. diam., bears S. 9° E., 189 lks. dist., mkd. T24S R7W S9 BT.

An oak, 12 ins. diam., bears S. 10½° W., 283 lks. dist., mkd. T24S R7W S8 BT.

A fir, 20 ins. diam., bears N. 69¾° W., 202 lks. dist., mkd. T24S R7W S5 BT.

From this point the witness point bet. secs. 4 and 9, established by Hathorn in 1857, bears N. 89° 40' E., 20.125 chs. dist., perpetuated and recorded by Deputy County Surveyor, James W. Byron, in 1960, monumented with an iron post, 1 in. diam., firmly set, protruding 18 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S R 7 W
S 4
S 9

WC
1960