

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 7 W.

CHAINS

from which the original bearing trees

A down fir, 50 ins. diam., bears N. 50° W., 35 lks. dist., no marks visible.

A down fir, 32 ins. diam., bears S. 50° E., 19 lks. dist., mkd. BT on opened blaze.

and bearing trees mkd. by Byron

A hemlock, 16 ins. diam., bears N. 30½° W., 73 lks. dist., with a healed double blaze.

A fir, 14 ins. diam., bears S. 20° E., 50 lks. dist., mkd. with a healed double blaze.

From this same point, the S 1/16 sec. cor. of secs. 8 and 9, established by Hathorn, in 1857, bears S. 0° 08' W., 60.41 chs. dist., perpetuated and recorded by Deputy County Surveyor James W. Byron, in 1960, monumented with an iron post, 1 in. diam., firmly set, protruding 16 ins. above the ground, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 24 S R 7 W

WC

S 8 | S 9

South 1/16

COR.

1960

from which the remaining original bearing tree

A burned fir snag, 28 ins. diam., bears S. 45° W., 31 lks. dist., mkd. BT on open blaze. (Record, 29 lks.)

and bearing trees mkd. by Byron

A fir, 16 ins. diam., bears S. 72° E., 10 lks. dist., mkd. S 1/16 S9 CS BT.

A fir, 13 ins. diam., bears N. 62½° W., 16 lks. dist., mkd. S 1/16 S8 CS BT.

N.0° 17' E., bet. secs. 4 and 5, marking and blazing the true line.

Descend 20 ft. along W. slope, through open prairie.

5.00 Enter timber, edge bears NW. and S. 20° E.

18.40 Spur, slopes NW.; desc. 90 ft. over N. slope.

20.15 Wire fence, bears E. and W.

20.40 Ravine, course W.; asc. 65 ft. over SW. slope.

23.70 Top of ascent, slopes W.; desc. 10 ft. along W. slope.

36.00 Bottom of descent, slopes W., and dirt road, 20 lks. wide, bears NW. and SE.; asc. 55 ft. over SW. slope.

37.80 Spur ridge, bears NW. and SE., and wire fence bears NW. and SE.; desc. 10 ft. over NE. slope.